FIFTH WHEEL HITCH CHECKLIST

DOWNLOAD OR PRINT AND LAMINATE FOR REFERENCE



1.	Check campsite for obstructions.	11.	Open security latch on fifth wheel hitch.
2.	Use a spotter when backing in.	12.	Pull hitch latch bar to disengage kingpin from the pin box.
3.	Position the fifth wheel on the campsite to be as level as possible.	13.	Disconnect the breakaway cable.
4.	Put tow vehicle in park and set the emergency brake.	14.	Raise landing legs to remove tongue weight from the hitch
5.	Place wheel chocks in front and back of tires.	15.	Drive truck slowly forward until rear bumper is clear of pin box.
6.	Set leveling pads under landing legs.	16.	Raise the truck tailgate.
7.	LOWER TRUCK TAILGATE.	17.	Push hitch latch bar into the closed position.
8.	Extend the fifth wheel landing legs until you	18.	Leave the security latch in the unlocked position.
	can see a crack of daylight between the hitch and pin box.	19.	Proceed to level and stabilize.
9.	Disconnect and store trailer electrical cable.	20.	Install a kingpin stabilizing jack under the front.
10.	Double-check that wheel chocks are firmly	21.	Securely stow all jack crank handles and other fifth wheel hitch attachments.
11.	in place. Remove lock or pin from the hitch.	22.	Remove extended tow mirrors from tow vehicles (if applicable).

Disclaimer: Some fifth wheel hitches have different/additional equipment. Use this checklist in conjunction with your hitch and fifth wheel owner's manuals.

