

MEDD-140 REFRIGERATOR



Characteristics

Structure	White version or Stainless steel 18/10 int.+ext.
Insulation thickness	40 (polyur. mm)
Doors number	1
Door type	Glass
Refrigeration type	Ventilated
Refrigerant type	R404A
Temperature range	+4°
Temperature control/ adjustment	Control: Door alarm, Temperature alarm, Dirty Condenser alarm, faulty condenser, Faulty evaporator, faulty sensor, RS485 In/Out, Memory of last 12 alarms
Defrosting type	Auto
Voltage	230V/1/50Hz
Castors	Standard fitted
Capacity (LT)	140
Safety key locking	Standard fitted
Internal lighting	Standard fitted
Digital monitor (Alarm system)	Standard fitted: - Back up battery (In case of power failure) - Temperature tracking with SD card incl. download interf. SW (memory of all temp Values and operation data, min 5 years) - 2 output relays (dry contact)
Drawers nr.	3
Storage capacity (blood bags nr., 450 ml)	63
Dimensions (cm)	52 x 64 x 100
Net weight (kg)	73

Automatic water evaporation.
Probe for product simulation.
Ext. terminal board for RS485/dry contacts.
Available also with fully insulated door.

Equipment in accordance with Directive 93/42/EEC annex V, article 3 and following modifications.

Accessories

- Printer
- GSM Communicator CF2008 module
- Drawer perspex front (H=83 mm)
- PT100 Extension module + nr.1 PT100 probe + 4-20mA output
- Pt100 probe
- Frequency 60Hz
- WEB LIGHT SERVER (Ethernet + GSM)
- Voltage 115V
- Remote panel

MEDDICATION INC.
Medical Equipment Solutions

100 Spectrum Center Drive,
Suite 900, Irvine, CA 92618
USA

www.meddicate.us
info@meddicate.us