



BLSH-1  -  -   
**(A) (B) (C)**

- A. Plating Options
  - See Plating Options below
- B. Shunt Style
  - 01= Low profile; Low insertion
- C. Lead Free

Plating options	
<input checked="" type="checkbox"/>	Gold Flash over Entire Pin

**Specifications:**  
 Current Rating: 3.0 Ampere  
 Insulation Resistance: 1000M Ohms Min.  
 Dielectric Withstanding: 600V AC  
 Contact Resistance: 20M Ohms Max.  
 Operation Temperature: -40°C to +105°C  
 Max. Process Temperature  
 Peak: 260°C up to 10 secs.  
 Process: 230°C up to 60 secs.  
 Wave: 260°C up to 6 secs.  
 Manual Solder: 350°C up to 5 secs.

**Materials:**  
 Contact Material: Phosphor Bronze  
 Insulator Material: Nylon  
 White Molded Plastic

Products cut to specific sizes are uncancellable/ nonreturnable.  
 Parts are subject to change without notice.



**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Major League Electronics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Major League Electronics IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME		DATE	
DIMENSIONS ARE IN INCHES		DRAWN	EOW	10/27/16	
TOLERANCES:		CHECKED	GWE	10/27/16	
ONE DECIMALS ±.100		ENG APPR.			
TWO DECIMAL ±.100		MFG APPR.			
THREE DECIMAL ±.005		INTERPRET GEOMETRIC TOLERANCING PER:		ADDRESS:	
FOUR DECIMAL ±.002		MATERIAL		2533 Centennial Blvd. Jeffersonville, In 47130	
NEXT ASSY	USED ON	FINISH		Phone: 812-670-4174	
APPLICATION		DO NOT SCALE DRAWING		Fax: 812-670-4175	
				E-Mail: mle@mlelectronics.com	
		TITLE: BLSH-1 SERIES		SIZE DWG. NO.	REV
		SCALE: 16:1		C	A
				SHEET 1 OF 1	