



MICRO - 06 - **XX** - **XX** - **X** - **LF**  
(A) (B) (C) (D)

- A. Pins Per Row  
- 2 through 10  
B. Packing Information  
- TR= Tape and Reel  
- TB= Tube  
C. Pad  
- P= Plastic  
- O= No Pad  
- If left blank, packaging at MLE's discretion  
Pad may be metal, mylar or plastic  
D. Lead Free

Mates With:  
MICRO-01 (Board to Board)  
MICRO-02 (Board to Board)  
MICRO-03 (Board to Board)

Specifications:  
Current Rating: 1.0 Ampere  
Insulation Resistance: 1000M Ohms Min.  
Withstanding Voltage: 500V AC/DC  
Contact Resistance: 20M Ohms Max.  
Operation Temperature: -40°C to +105°C

Materials:  
Contact Material: Phosphor Bronze  
Insulator Material: High Temperature Plastic PA46 (UL94V-0), Red  
Contact Plating: Sn Over Ni

Termination:  
PCB

Pins Per Row	Dimension		Qt'y/ Tube	Qt'y/ Tube
	A	B		
2	7.20	2.54	71	500
3	9.74	5.08	54	500
4	12.28	7.62	44	500
5	14.82	10.16	37	500
6	17.36	12.70	31	500
7	19.90	15.24	28	500
8	22.44	17.78	25	500
9	24.98	20.32	22	500
10	27.52	22.86	20	500

Tails may be clipped to achieve specific dimensions.  
Products cut to specific sizes are uncancellable/ nonreturnable.  
Parts are subject to change without notice.



PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Major League Electronics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Major League Electronics IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED: <b>DIMENSIONS ARE IN INCHES</b> <b>TOLERANCES:</b> ONE DECIMALS ±.100 TWO DECIMAL ±.010 THREE DECIMAL ±.005 FOUR DECIMAL ±.002		DRAWN: EOW 04/07/14 CHECKED: GWE 04/07/14 ENG APPR: MFG APPR:	NAME: DATE: 2533 Centennial Blvd. Jeffersonville, IN 47130 Phone: 812-670-4174 Fax: 812-670-4175 E-Mail: mle@mlelectronics.com		TITLE: MICRO-06 Series SIZE: DWG. NO. <b>C</b> SCALE 12:1	REV <b>B</b> SHEET 1 OF 1
NEXT ASSY USED ON APPLICATION	FINISH DO NOT SCALE DRAWING	INTERPRET GEOMETRIC TOLERANCING PER:	ADDRESS:			