



TBR - 03 - - - -
(A) (B) (C) (D)

- A. Pitch**
- 197= .197(5.00) cl
- B. No. of Positions**
- 02-24
- C. Color**
- GR= Green (Standard)
- BK= Black
- BL= Blue
- WH= White
- GY= Grey
- OR= Orange
- YW= Yellow
- RD= Red
- BR= Brown
- D. Lead Free**
- Specifications:**
Current Rating: 10 Ampere
Voltage Rating: AC 250V
Wire Range: 14-26 AWG
Insulation Resistance: DC 500V 1000Mohm
Dielectric Withstanding Voltage: AC 2500V/1 minute
Operation Temperature: -33°C to +105°C
Max. Torque: 3.47 lb-in (4.0kgf. cm)
Strip Length: .236-.315(6-8mm)
- Materials:**
1. Body: PA66 (Nylon), UL94V-0
2. Screw: M3.0, C1018 Steel, Zinc Plated
3. Contact: Brass, Nickel Plated
4. Terminal: Brass, Tin Plated

Tails may be clipped to achieve specific dimensions.
Products cut to specific sizes are uncancellable/ nonreturnable.
Parts are subject to change without notice.



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Major League Electronics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Major League Electronics IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
DRAWN	EOW	04/17/14		
CHECKED	GWE	04/17/14		
ENG APPR.				
INTERPRET GEOMETRIC TOLERANCING PER:		ADDRESS:		TITLE: TBR-03-197 Series
MATERIAL:		2533 Centennial Blvd. Jeffersonville, In 47130 Phone: 812-670-4174 Fax: 812-670-4175 E-Mail: mle@mlelectronics.com		SIZE DWG. NO. C
NEXT ASSY	USED ON	FINISH		REV A
APPLICATION	DO NOT SCALE DRAWING			SCALE 8:1 SHEET 1 OF 1