




Recommended P.C. Board Layout
SCALE 4:1






APPLICATION




TSHSCM-2 **XX** - **X** - **XXX** - **XX** - **XX** - **X** - **XXX** - **X** - **XX** - **X** - **XX** - **LF**
(A) (B) (C) (D) (E) (F) (G) (H) (I) (J) (K) (L)

- A. Pins Per Row
- 1 through 40
- B. Row Specification
- S= Single Row
- D= Double Row
- C. Desired Post Height
- Please specify tail length
- e.g. .100 [2.54] = 100
- D. Pin Options
- See Pin Options below
- E. Plating Options
- See Plating Options below
- F. Vertical
- G. Polarized Position
- Leave blank if not needed
- If required, specify empty pin position
- e.g. 012 for Pin 12
- H. Footprint (Option only for Single Row)
- S= pin 1 left
- M= pin 1 right
- I. Packing Information
- TR= Tape and Reel
- TB= Tube
- J. Pad
- P= Plastic
- O= No Pad
- If left blank, packaging at MLE's discretion
- Pad may be metal, mylar or plastic
- K. Alignment Pin (Option only for Double Row)
- Leave blank if not needed
- AP= with
- L. Lead Free

Mates with:
BCSS.
BSSH.
BSSHC.
BSSQ.
BSSQC.
BSSQM.
LSMBC.
LSSHSM.
SMBC.
SSHQ.
SSHQR.
SSHR.
SSHS.
SSHSM.
ULSMBC.



SINGLE (M) ROW



DOUBLE ROW

Plating options	
G	-10µ Gold on Contact Area/ Flash on Tail
T	-Matte Tin all Over
GT	-10µ Gold on Contact Area/ Matte Tin on Tail
H	-30µ Gold on Contact Area/ Matte Tin on Tail
F	-Gold Flash over Entire Pin
FT	- Gold Flash on Contact Area/ Matte Tin on Tail

Pin Options	
Max. Post Height	
.065 [1.65mm]	01
.088 [2.24mm]	02
.126 [3.20mm]	04
.156 [3.96mm]	06
.185 [4.70mm]	08
.210 [5.33mm]	10
.230 [5.84mm]	16
.250 [6.35mm]	20
.289 [7.34mm]	21
.388 [9.86mm]	30
.408 [10.36mm]	34
.427 [10.85mm]	35
.447 [11.35mm]	36

Specifications:
Current Rating: 3.0 Ampere
Insulation Resistance: 1000M Ohms Min.
Dielectric Withstanding: 500V AC
Contact Resistance: 20M Ohms Max.
Operation Temperature: -40°C to +105°C
Max. Process Temperature
Peak: 260°C up to 10 secs.
Process: 230°C up to 60 secs.
Wave: 260°C up to 6 secs.
Reflow: 260°C up to 10 secs.
Manual Solder: 350°C up to 5 secs.

Materials:
Contact Material: Phosphor Bronze
Insulator Material: Nylon 6T
Plating: Au or Sn over 50µ" (1.27) Ni

Tails may be clipped to achieve specific dimensions.
Products cut to specific sizes are uncancellable/ nonreturnable.
Parts are subject to change without notice.

UNLESS OTHERWISE SPECIFIED:		NAME		DATE		TITLE: TSHSCM-2-V SERIES		
DIMENSIONS ARE IN INCHES		DRAWN	EOW	02/23/15		SIZE	DWG. NO.	REV
TOLERANCES:		CHECKED	GWE	02/23/15		C		C
ONE DECIMALS ±.100		ENG APPR.						
TWO DECIMAL ±.010		MFG APPR.						
THREE DECIMAL ±.005		ADDRESS:		2533 Centennial Blvd.				
FOUR DECIMAL ±.002		MATERIAL:		Jeffersonville, IN 47130				
NEXT ASSY		FINISH		Phone: 812-670-4174				
USED ON		DO NOT SCALE DRAWING		Fax: 812-670-4175				
APPLICATION				E-Mail: mle@mlelectronics.com				
						SCALE 8:1		
						SHEET 1 OF 1		

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Major League Electronics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Major League Electronics IS PROHIBITED.

