

## **Submittal Page**

Model: Ventus X 24k-220V IVKH241B - OVKH241B

## hvacmirage.us

Job name:
Location:
Engineer:
Submitted to:
Submitted by:
Reference:
Approval:
Date:
Construction:
Unit #:
Drawing #:

Туре			cooling&heating
Control type			remote
Power supply			230V~/60Hz/1P
Rated Cooling (95°F/35°C)	Rated cooling capacity (95°F)	Btu/h	24000
	EER <sup>2</sup> (95°F)	Btu/W.h	10.0
	SEER <sup>2</sup>	Btu/W.h	19.0
Rated Heating	Rated Heating capacity (47°F)	Btu/h	24400
	HSPF <sup>2</sup> Rating (Region IV)	Btu/W.h	8.5
	HSPF <sup>2</sup> Rating (Region V)	Btu/W.h	7.0
	COP <sup>2</sup> (47°F)	W/W	3.21
	COP <sup>2</sup> (5°F)	W/W	1.75
Rated Input Consumption	Cooling	W	2360
	Heating	W	2230
Rated Current	Cooling	Α	11.0
	Heating	Α	10.5
Moisture Removal		Liters/h	2.6
Indoor Noise Level at Cooling	Turbo/High/Med/Low/Mute		51/48/43/38/35
Outdoor Noise Level	-	dB(A)	58
Connecting Wiring	Size x Core number		4×16AWG
Indoor Motor	Motor Type		DC
	Output	W	45
	Speed	rpm	1150/950/800
Indoor Air Circulation/Hi		CFM	847/700/641
Compressor	Brand		SANYO
	Oil / Oil Amount		FV68S, 450CC
Outdoor Motor	Motor Brand		Broad-Ocean
	Motor Type		DC
	Output	W	85
Connecting Pipe	Gas	inch	1/2"
	Liquid	inch	1/4"
Net Dimensions (W x D x H)	Indoor	inch	46.93x14.17x10.23
	Outdoor	inch	33.26x14.96x27.51
Net Weight	Indoor	ibs	36.4
	Outdoor	ibs	90.4
Packing Dimensions (W x D x H)	Indoor	inch	49.80x17.13x13.27
	Outdoor	inch	37.79x16.92x29.53
Gross Weight	Indoor	ibs	45.2
	Outdoor	ibs	104.7
Ambinet Temperature	Indoor (cooling/heating)	°F	>=62/<=86
	Outdoor (cooling/heating)	°F	'5~122/-4~86
Max Fuse		A	30
Max Ope. Press		PSIG	550
Maximum Allowed Length		ft	65
Maximum Allowed Height		ft	49



## **Submittal Page**

Model: Ventus X 24k-220V IVKH241B - OVKH241B











