



MIRAGE

Think **smart**. Think **cool**. Think **Mirage**.

hvacmirage.us

Job name: _____

Location: _____

Engineer: _____

Submitted to: _____

Submitted by: _____

Reference: _____

Approval: _____

Date: _____

Construction: _____

Unit #: _____

Drawing #: _____

Submittal Page

Model: Ventus X 36k-220V
IVKH361B - OVKH361B

Type			cooling&heating
Control type			remote
Power supply			208/230V~/60Hz/1P
Rated Cooling (95°F/35°C)	Rated cooling capacity (95°F)	Btu/h	36000
	EER ² (95°F)	Btu/W.h	9.0
	SEER ²	Btu/W.h	19.0
Rated Heating	Rated Heating capacity (47°F)	Btu/h	36000
	HSPF ² Rating (Region IV)	Btu/W.h	8.5
	HSPF ² Rating (Region V)	Btu/W.h	7.0
	COP ² (47°F)	W/W	3.01
	COP ² (5°F)	W/W	1.75
Rated Input Consumption	Cooling	W	3850
	Heating	W	3500
Rated Current	Cooling	A	16.5
	Heating	A	15.2
Moisture Removal		Liters/h	3
Indoor Noise Level at Cooling	Turbo/High/Med/Low/Mute		52/49/43/38/36
Outdoor Noise Level			dB(A) 63
Connecting Wiring	Size x Core number		4×16AWG
Indoor Motor	Motor Type		DC
	Output	W	45
	Speed	rpm	1150/950/800
Indoor Air Circulation/Hi		CFM	847/700/588
Compressor	Brand		GMCC
	Oil / Oil Amount		VG74, 620CC
Outdoor Motor	Motor Brand		Broad-Ocean
	Motor Type		DC
	Output	W	85
Connecting Pipe	Gas	inch	5/8"
	Liquid	inch	1/4"
Net Dimensions (W x D x H)	Indoor	inch	46.93x14.17x10.23
	Outdoor	inch	35.83x14.17x31.50
Net Weight	Indoor	lbs	39.7
	Outdoor	lbs	114.6
Packing Dimensions (W x D x H)	Indoor	inch	49.80x17.13x13.27
	Outdoor	inch	40.47x18.70x33.86
Gross Weight	Indoor	lbs	48.5
	Outdoor	lbs	132.3
Ambient Temperature	Indoor (cooling/heating)	°F	>=62/<=86
	Outdoor (cooling/heating)	°F	'5~122/-4~86
Max Fuse		A	35
Max Ope. Press		PSIG	550
Maximum Allowed Length		ft	98
Maximum Allowed Height		ft	65

