



## COMPACT ON-A-WALL

### PLF3CM, PLF5CM, PLFCM



### Suggested Specification

Cabinet finish shall be Sandstone powder coated paint on galvanized steel or brushed stainless steel. Cooling system shall use R-134a refrigerant. Shall be listed by Underwriter's Laboratories to U.S. and Canadian standards and conform to European Union Directives.

### Models

**PLF3CM** delivers 2.5 gph of chilled drinking water.

**PLF5CM** delivers 4.7 gph of chilled drinking water.

**PLCM** is a non-refrigerated fountain.

### Standard Features

- Waterways are Lead-Free in Material & Construction
- Dial-A-Drink® Bubbler
- Stainless Steel Top
- Welded, Heavy-Gauge Steel Frame
- High-Efficiency Cooling Tank and Coil
- Refrigerant 134a
- Limited 5-Year Warranty

### Finishes

- Standard Cabinet Finish: Sandstone powder coated paint on Galvanized steel.
- Optional finishes at extra cost: Stainless Steel, Powder coated paint.

### Installation

- Prior to roughing-in, consult local, state and federal codes for proper mounting height.
- Ship with complete instructions and wall mounting bracket.
- Removable panels provides easy access for installation.

**Limited 5-Year Warranty** (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most components parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty:** One year on the sealed refrigeration system and most components parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Models covered by this specification complies with all known Plumbing Codes. Listed by Underwriter's Laboratories to U.S. and Canadian standards and conform to European Union Directives.



Components in these water coolers are lead free as defined by the Safe Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.



Model	50° F Drinking Water 90° F Ambient Air Temp*			Hot'N Cold™ Model	115 Volts, 60HZ			Glass Filler Acc. Option	Cabinet Color Option	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
PLF3CM**	2.5	2.5	NO	NO	1/8	2.1	160	NO	YES	49 Lbs.
PLF5CM**	4.7	2.5	YES	NO	1/8	2.1	160	NO	YES	51 Lbs.
PLFCM	Fountain Only							NO	YES	24Lbs.

\*Air Conditioning and Refrigerant Institute Standard Rating Condition 80° F inlet water temperature.

\*\* Special export models available, operable on 220-240 volts, 50 Hertz. cULus certification not applicable.

# OASIS® COMPACT ON-A-WALL WATER COOLER MODELS PLF3CM, PLF5CM, PCM

