

[Home](#) ▶ [Equipment](#) ▶ [Excavators](#) ▶ [Compact Excavators](#) ▶ [E10](#)

E10

Compact Excavator



Access jobsites where hand labor is your only other option.

- Ultra-compact design
- Retracted 28-inch track width
- Zero tail swing

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)

[Find Dealer](#)

[Download Brochure](#)



E10 Overview

- With a retracted track width of 28 inches, the ultra-compact Bobcat® E10 compact (mini) excavator allows you to easily navigate through narrower openings and operate in tighter conditions.
- Zero tail swing offers the greatest flexibility to slew and deposit spoil while offering the most protection against jobsite obstacles.
- Pass underneath branches, low openings and through doorways to get to your work area.

E10 Specifications

E10 Key Specifications

Horsepower	10.2 hp
Operating Weight	2,593 lb
Bucket Digging Force	1,865 lbf
Maximum Reach at Ground Level	10.2 ft

Width	28 in
Tail Swing Type	Zero

Engine

Emissions Tier (EPA)	Tier 4
Engine Fuel	Diesel
Maximum Governed RPM	2,370 rpm
Horsepower	10.2 hp
Turbocharged Engine	no
Optional Turbocharged Engine	N/A

Performance

Operating Weight	2,593 lb
Weight Class	1 t
Travel Speed - High	1.7 mph
Travel Speed - Low	1.3 mph
Arm Digging Force	1,248 lbf
Bucket Digging Force	1,865 lbf
Rated Lift Capacity	965 lb
Lift Radius	79 in
Boom Swing - Left	67°
Boom Swing - Right	64°
Maximum Dig Depth	6 ft
Max Dump Height	6 ft
Maximum Reach at Ground Level	10.2 ft

Capacities

Fuel Tank	4.2 gal
-----------	---------

Hydraulic System

Auxiliary Std Flow	5.3 gal/min
Auxiliary Pressure	2,756 psi

Dimension

Length	110 in
--------	--------

Overall Length in Travel Position	110 in
Width	28 in
Height	87 in
Height with Operator Cab	87 in

Features	
Air Conditioning	Not Applicable
Cab Enclosure	Not Applicable
Cab Heater	Not Applicable
Heater Air Conditioning	Not Applicable
Radio	Not Applicable
Tail Swing Type	Zero
Engine Shutdown	Not Applicable
Auxiliary Hydraulics	Standard
Secondary Auxiliary Hydraulics	Not Applicable
Quick Tach System	Not Applicable
Rubber Track	Standard
Selectable Auxiliary Hydraulic Flow	Not Applicable
Angle Blade	Not Applicable

E10 Features & Benefits

[Expand all](#)

- Performance** 4
- Comfort** 6
- Uptime Protection** 5
- Serviceability** 1

E10 Attachments

[View All Attachments](#)



Bucket - Grading, 32"

Smooth lip for finish grading, cleaning ditches, backfilling and leveling.



Bucket - Trenching, 418, 12" (Pin-On)

Dig narrow, deep trenches while maintaining excellent breakout force and fast cycle times.



Bucket - Trenching, 418,

Dig narrow, deep trenches while maintaining excellent breakout force and fast cycle times.



WARNING: This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.