

Performance

Tipping load (ISO 14397-1)	1888 kg
Rated operating capacity (ISO 14397-1)	944 kg
Pump capacity	64.70 L/min
Pump capacity (with high flow option)	101.10 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range - option)	17.3 km/h
Max. travel speed (low range)	11.8 km/h

Engine

Make / Model	Kubota / V2607-DI-T-E3B-BC-2
Fuel	Diesel
Cooling	Liquid
Maximum power at 2700 RPM (SAE J1995)	45.5 kW
Torque at 1425 RPM (SAE J1995 Gross)	201.0 Nm
Number of cylinders	4
Displacement	2600 cm ³
Fuel tank	93.70 L

Weights

Operating weight	2900 kg
Shipping weight	2560 kg

Controls

Vehicle steering	Direction and speed controlled by two hand levers
Loader hydraulics tilt and lift	Separate foot pedals or Selectable Joystick Controls (SJC)
Front auxiliary (standard)	Electrical switch on right-hand steering lever

Drive System

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---


Standard Features

Standard Seat	Lift arm support
Automatically activated glow plugs	Work lights, front and rear
Auxiliary hydraulics: variable flow/maximum flow	Parking brake
Bob-Tach™ frame	Seat belt
Bobcat Interlock Control System (BICS)	Seat bar
Standard Cab	Spark arrestor muffler
Electrically activated proportional front auxiliary hydraulics	10 x 16.5, 10-ply, Heavy duty tyres
Engine/hydraulics system shutdown	EAC certification
Manual	Warranty: 24 months or 2000 hours (whichever occurs first)

Options

High-Flow hydraulics	2 Speed
Deluxe instrument panel	Air ride seat with 2 point seat belt
Power Bob-Tach™	Back-up alarm
Deluxe pressurized cab with heating	Beacon
10 x 16.5, 10-ply, Heavy duty tyres, offset rims	Bucket positioning valve
10 x 16.5, 10-ply, Severe duty tyres	Engine block heater
12 x 16.5, Solid flex tyres	Fire extinguisher
31 x 12-16.5, 10-ply, Superflotation tyres, offset rims	Radio
Advanced Control System (ACS)	Road kit
Selectable Joystick Controls (SJC)	Strobe
Hydraulic bucket positioning (including ON/OFF switch)	

Dimensions



(A) 3901.0 mm	(J) 3023.0 mm
(B) 1970.0 mm	(K) 828.0 mm
(C) 24.2°	(L) 42.0°
(D) 185.0 mm	(M) 97.0°
(E) 1082.0 mm	(N) 1727.0 mm
(F) 2657.0 mm	(O) 2024.0 mm
(G) 3378.0 mm	(P) 1374.0 mm
(H) 30.0°	(Q) 1643.0 mm
(I) 2319.0 mm	

Attachments

Angle Brooms	Pallet Fork Accessories
Auger Accessories	Pallet Forks, Hydraulic
Augers	Planer Accessories
Backhoes	Planers
Bale Forks	Root Grapples
Box Blades	Rotary Grinders
Breaker Accessories	Scarifiers
Breakers	Scrapers
Brushcat™ Rotary Cutters	Skeleton Buckets
Brush Saws	Snow & Light Material
Combination Buckets	Buckets
Concrete Mixers	Snow Blades
Concrete Pumps	Snow Pushers
Construction / Industrial	Snow V-Blades
Buckets	Sod Layers
Diggers	Soil Conditioners
Dozer Blades	Spreaders
Drop Hammers	Steel Tracks
Dumping Hoppers	Stump Grinders
Fertilizer and Grain Buckets	Sweepers
Flail Cutters	Tillers
General Purpose (GP)	Tilt-Tatch
Bucket	Tree Transplanters
Graders	Trench Compactors
Grapples, Industrial	Trenchers
Landplanes	Utility Forks
Landscape Rakes	Vibratory Rollers
Laser Equipment	Wheel Saws
Low Profile Buckets	Whisker Brooms
Miscellaneous	Wood Chippers
Mixing Buckets	
Mowers	