

E32

Compact Excavator



The E32 features unmatched power and a narrow stance.

- Powerful performance and maneuverability
- Conventional tail swing
- Ideal for restrictions like doors and gates
- Various arm options

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)

[Find Dealer](#)



[Download Brochure](#)

E32 Overview

- The Bobcat® E32 compact (mini) excavator packs powerful performance and maneuverability into a conventional tail swing design.
- Narrower than the E35, this machine is ideal if you frequently work around areas with space restrictions such as doors or gates.
- Boost your working range with the long arm option or a clamp-ready extendable arm option.

E32 Specifications

	E32	E32 (Long Arm)	E32 (Extendable Arm)
E32 Key Specifications			
Horsepower	24.8 hp	24.8 hp	24.8 hp
Operating Weight	7,403 lb	8,269 lb	8,497 lb
Bucket Digging Force	7,284 lbf	7,284 lbf	7,284 lbf

Maximum Reach at Ground Level	16.2 ft	17.2 ft	18.8 ft
Width	61.8 in	61.8 in	61.8 in
Tail Swing Type	Conventional	Conventional	Conventional

Engine			
Emissions Tier (EPA)	Tier 4	Tier 4	Tier 4
Engine Fuel	Diesel	Diesel	Diesel
Maximum Governed RPM	2,450 rpm	2,450 rpm	2,450 rpm
Horsepower	24.8 hp	24.8 hp	24.8 hp
Turbocharged Engine	no	no	no
Optional Turbocharged Engine	N/A	N/A	N/A

Performance			
Operating Weight	7,403 lb	8,269 lb	8,497 lb
Weight Class	3.4 t	3.8 t	3.9 t
Travel Speed - High	2.9 mph	2.9 mph	2.9 mph
Travel Speed - Low	1.6 mph	1.6 mph	1.6 mph
Arm Digging Force	4,690 lbf	4,074 lbf	4,592 lbf
Bucket Digging Force	7,284 lbf	7,284 lbf	7,284 lbf
Rated Lift Capacity	2975 lb	2871 lb	2733 lb
Lift Radius	118 in	118 in	118 in
Boom Swing - Left	75°	75°	75°
Boom Swing - Right	55°	55°	55°
Maximum Dig Depth	10.2 ft	11.1 ft	12.8 ft
Max Dump Height	11.4 ft	12 ft	12.9 ft
Maximum Reach at Ground Level	16.2 ft	17.2 ft	18.8 ft

Capacities			
Fuel Tank	13.7 gal	13.7 gal	13.7 gal

Fuel Tank	18.7 gal	18.7 gal	18.7 gal
Hydraulic System			
Auxiliary Std Flow	16.9 gal/min	16.9 gal/min	16.9 gal/min
Auxiliary Pressure	2,987 psi	2,987 psi	2,987 psi
Dimension			
Length	183.7 in	187.3 in	187.6 in
Overall Length in Travel Position	183.7 in	187.3 in	187.6 in
Width	61.8 in	61.8 in	61.8 in
Height	96.2 in	96.2 in	96.2 in
Height with Operator Cab	96.2 in	96.2 in	96.2 in

Features			
Air Conditioning	Optional	Optional	Optional
Cab Enclosure	Optional	Optional	Optional
Cab Heater	Not Applicable	Not Applicable	Not Applicable
Heater Air Conditioning	Optional	Optional	Optional
Radio	Optional	Optional	Optional
Tail Swing Type	Conventional	Conventional	Conventional
Engine Shutdown	Standard	Standard	Standard
Auxiliary Hydraulics	Standard	Standard	Standard
Secondary Auxiliary Hydraulics	Optional	Optional	Optional
Quick Tach System	Standard	Standard	Standard
Rubber Track	Standard	Standard	Standard
Selectable Auxiliary Hydraulic Flow	Standard	Standard	Standard
Angle Blade	Not Applicable	Not Applicable	Not Applicable

E32 Features & Benefits

Expand all ▾

Performance 12 ▾

Comfort 2 ▾

Uptime Protection 9 ▾

Serviceability 2 ▾

E32 Attachments

[View All Attachments >](#)



WARNING: *This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.*

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.