

### Performance

Tipping load (ISO 14397-1)	2359 kg
Rated operating capacity (ISO 14397-1)	1184 kg
Pump capacity	66.50 L/min
Pump capacity (with high flow option)	101.80 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range - option)	17.3 km/h
Max. travel speed (low range)	11.8 km/h

### Engine

Make / Model	Bobcat 2.4L, 97/68 EC Stage V
Fuel	Diesel
Cooling	Liquid
Power at 2600 RPM	54.5 kW
Torque at 1425 RPM (SAE J1995 Gross)	266.3 Nm
Number of cylinders	4
Displacement	2400 cm <sup>3</sup>
Fuel tank	93.70 L

### Weights

Operating weight	3271 kg
Shipping weight	2939 kg

### Controls

Vehicle steering	Direction and speed controlled by Selectable Joystick Controls (SJC) or two hand levers
Loader hydraulics tilt and lift	Selectable Joystick Controls (SJC) or separate foot pedals
Front auxiliary (standard)	Electrical switch on right-hand steering lever

### Drive System

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---

### Standard Features

10 x 16.5, 10-ply, Heavy duty tyres	Horn
3 Point Seat belt	Key start
5" Deluxe Instrumentation (Radio Ready)	LED Working Lights front and rear
Adjustable suspension seat	Lift arm support
Auxiliary hydraulics: variable flow/maximum flow	Manual
Backup Alarm	Parking brake
Bobcat Interlock Control System (BICS)	Seat bar
Bob-Tach™ Attachment System	Selectable Joystick Controls (SJC)
Deluxe pressurized cab with HVAC	Spark arrestor muffler
Dual Direction Bucket Positioning (including ON/OFF switch)	Two speed travel
Engine/hydraulics system shutdown	Warranty: 24 months or 2000 hours (whichever occurs first)
High flow hydraulics	Machine IQ (telematic)


### Options

10 x 16.5, 10-ply, Heavy duty tyres, offset rims	Clear View Cab
10 x 16.5, 10-ply, Severe duty tyres	Heated Cloth Air ride seat with 3 point seat belt
12 x 16.5, Solid flex tyres	Manual Hand and Foot Controls
31 x 12-16.5, 10-ply, Superflotation tyres, offset rims	Power Bob-Tach™
7" Touch Display (Integrated Bluetooth, Hands Free Calling, Radio, Reversing Camera)	Radio
Auto HVAC	Reversible Fan
Auto Ride Control	Reversing Camera
Beacon	Strobe

### Environmental

Operator LpA(98/37 & 474-1)	78 dB(A)
Noise level LWA(EU Directive 2000/14/EC)	101 dB(A)
Whole body vibration (ISO 2631-1)	0.76 ms <sup>-2</sup>
Whole body vibration uncertainty	0.38 ms <sup>-2</sup>
Hand-arm vibration (ISO 5349-1)	0.76 ms <sup>-2</sup>

### Dimensions



(A) 3909.6 mm	(J) 3048.0 mm
(B) 2044.7 mm	(K) 803.1 mm
(C) 25.0°	(L) 37.0°
(D) 213.7 mm	(M) 94.0°
(E) 1133.3 mm	(N) 1727.2 mm
(F) 2717.8 mm	(O) 2033.4 mm
(G) 3427.0 mm	(P) 1406.6 mm
(H) 30.0°	(Q) 1641.5 mm
(I) 2395.8 mm	

### Attachments

Angle Brooms	Pallet Fork Accessories
Auger Accessories	Pallet Forks, Hydraulic
Augers	Planer Accessories
Backhoes	Planers
Bale Forks	Root Grapples
Box Blades	Rotary Grinders
Breaker Accessories	Scarifiers
Breakers	Scrapers
Brushcat™ Rotary Cutters	Skeleton Buckets
Brush Saws	Snow & Light Material
Combination Buckets	Buckets
Concrete Mixers	Snow Blades
Concrete Pumps	Snow Pushers
Construction / Industrial	Snow V-Blades
Buckets	Sod Layers
Diggers	Soil Conditioners
Dozer Blades	Spreaders
Drop Hammers	Steel Tracks
Dumping Hoppers	Stump Grinders
Fertilizer and Grain Buckets	Sweepers
Flail Cutters	Tillers
Graders	Tilt-Tatch
Grapples, Industrial	Tree Transplanters
Landplanes	Trench Compactors
Landscape Rakes	Trenchers
Laser Equipment	Utility Forks
Low Profile Buckets	Vibratory Rollers
Miscellaneous	Wheel Saws
Mixing Buckets	Whisker Brooms
Mowers	Wood Chippers