



MT100

Mini Track Loader

No need for wheelbarrows, shovels or other hand tools when you roll onto jobsites with the Bobcat® MT100 mini track loader.

- Fit through gates, doorways and other narrow spaces
- 1,000 lb. rated operating capacity
- Powerful breakout force and impressive lift height

Buy now and get 0% financing for up to 24 months*, or, in lieu of financing, choose a cash rebate of \$400 USD*/\$500 CAD*.

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)

[Find Dealer](#)

[Download Brochure](#)

MT100 Overview

- The MT100 travels through gates, doorways and other narrow spaces with ease.
- The machine also delivers a big boost in power with a 1,000-pound rated operating capacity, powerful breakout force and impressive lift height.
- The optimized roller spacing on the MT100’s track system improves ride quality for enhanced operator comfort and confidence when working long days.
- Easy, tool-free access to maintenance areas and advanced safety features, including neutral start interlocks, are standard on the MT100 mini track loader, while sealed rollers eliminate the need for daily roller maintenance and decrease downtime.
- This loader also features high-flotation tracks that allow it to move across wet and muddy ground.

MT100 Specs & Compare

MT100 Key Specifications	
Rated Operating Capacity (ISO)	1,000 lb
Carry Position ROC with Standard Counterweight -UnderCarriage Position	1,300 lb
Operating Weight	3390 lb
Ground Pressure (Rubber)	5.25 psi
Auxiliary Std Flow	12 gal/min
Width	35.6 in
Height to Bucket Hinge Pin	80.9 in
Engine	

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	55 in³
Number of Cylinders	3
Horsepower	24.8 hp

Performance	
Rated Operating Capacity (ISO)	1,000 lb
Carry Position ROC with Standard Counterweight -UnderCarriage Position	1,300 lb
Tipping Load	2898 lb
Operating Weight	3390 lb
Ground Pressure (Rubber)	5.25 psi
Travel Speed	4.1 mph
Travel Speed - Reverse	2.9 mph

Capacities	
Fuel Tank	7 gal

Hydraulic System	
Pump Capacity	12 gal/min
System Relief @ Quick Couplers	2,900 psi
Auxiliary Std Flow	12 gal/min

Dimension	
Length	106.2 in
Width	35.6 in
Height	54.6 in
Height to Bucket Hinge Pin	80.9 in
Length of track on ground	41.4 in
Reach @ Maximum Height	18.6 in

Features	
Lift-Arm Support	Standard
Auxiliary Hydraulics	Standard
Spark Arrestor Muffler	Standard
Bob-Tach Attachment System	Standard
Reverse Travel Stop Panel	Not Applicable
Wide Track	Optional
Neutral Start Interlocks	Standard
Lift Arm Lockout With Manual Bypass	Standard
Tilt Lockout	Standard
Built-In Tie Down & Crane/Lift Locations	Standard
Ride-on Platform	Standard

MT100 Features & Benefits

Expand all

- Versatility 3
- Comfort 4
- Serviceability 2

MT100 Attachments

[View All Attachments >](#)



Angle Broom - 48"

Clear away dirt, dried mud, light snow and other debris.

[View Attachment >](#)



Angle Broom - 52"

Clear away dirt, dried mud, light snow and other debris.

[View Attachment >](#)



Angle Broom - 64"

Clear away dirt, dried mud, light snow and other debris.

[View Attachment >](#)



*The prices advertised are suggested resale prices that Bobcat recommends to dealers for purposes of trying to ensure that Bobcat’s products are price-competitive and that dealers have the proper incentives to market and service the products in accordance with Bobcat’s brand standards. Bobcat reserves the right to change suggested resale prices, product specifications, and options at any time. The final sales price is determined independently by the selling dealer in its sole discretion. Pricing is country specific. Bobcat’s suggested list prices are for products sold in the US only. Product configuration may differ from image(s) provided. See dealer for full product details.

*Offer ends 12/31/2023. Available at participating and eligible dealers only. Offer may vary by product type, series, model and select units in dealer's current inventory. Must take delivery from dealer stock by 12/31/2023. Offers available on new equipment in US and Canada only. Some restrictions apply. Length of contract and rate may vary. Monthly payment subject to change. Prior purchases not eligible. See dealer for details. Financing provided on approval of credit by authorized Bobcat finance providers to well-qualified buyers. All finance programs and rates are subject to final approval by the applicable Bobcat finance provider and are subject to change at any time without notice. Administrative fees may apply. Offer not available to government accounts, national accounts and municipal/utility bid customers. Bobcat Company reserves the right to extend or discontinue any of these programs at any time without prior notice.



WARNING: This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.