AVIN Automotive Series

PC/LD Engine Oils



Technical Data Sheet

POWER 1

SAE 10W-40

API SN/SM/CF; ACEA A3/B3, A3/B4; VW 501.01/505.00; MB 229.3/226.5; RENAULT RN 0700/0710

SAE 15W-40

API SN/SL/CF; ACEA A3/B3, A3/B4; VW 505.00/501.01; MB 229.1

Description

Power 1 is a Top-tier synthetic lubricant, suitable for modern petrol, diesel and LPG engines, either turbocharged or not.. Blended with additives that enhance its overall performance, it provides excellent oxidation resistance, optimal lubrication in cold start and ultimate protection. In addition, POWER 1 oil meets the requirements of top engine manufacturers.

Functional Characteristics

Prevents sludge and deposits formation

Protection against corrosion and wear.

Good anti-rust properties.

Prolonged change oil intervals.

Typical Use

Suitable for modern petrol, diesel and LPG engines, either turbocharged or not, they meet the requirements of all major engine manufacturers..

Typical Characteristics

POWER 1		
SAE	10W-40	15W-40
Specific gravity at 15°C/4°C	0,863	0,876
Viscosity at 40°C, cst	90,0	92,0
Viscosity at 100°C, cst	14,0	13,5
Viscosity Index	157	140
Flash Point (C.O.C.), °C	230	240
Pour Point, °C	-30	-30
TBN	10,2	10,2