

SR6

SR6 is made for use during low-pressure, textile reinforced applications that include petroleum and water-based fluids for use as power steering return, lube lines and air lines. This hose is not intended for brake applications.



PERFORMANCE + SPECS

Meets or exceeds the performance requirements of:

SAE 100R6
EN 854 R6

Inner Tube
NBR (Nitrile)

Reinforcement
One textile braid

Cover
Black CR (Polychloroprene)
Sizes 03 - 06: Wrapped Cover
Sizes 08 - 12: Smooth Cover

Temperature Range
-40 F to 212 F (-40 C to 100 C)

KEY FEATURES

4:1 4:1 Safety Factor

BRANDING

SR6 08 SAE 100R6 / EN 854 R6 1/2" (DN12) **400 PSI (2.8 MPa)**

Part Number	SAP Number	Hose Size ID	Hose OD	Hose OD	Max. Working Pressure	Max. Working Pressure	Min. Bend Radius	Min. Bend Radius	Weight	Fitting
		in.	in.	mm	psi	MPa	in.	mm	lbs./ft.	
SR6-03	20240277	3/16	0.44	11.1	500	3.4	2.0	51	0.07	UC
SR6-04	20240278	1/4	0.50	12.7	400	2.8	2.5	64	0.09	UC
SR6-05	20240279	5/16	0.56	9.1	400	2.8	3.0	76	0.09	UC
SR6-06	20240280	3/8	0.63	15.9	400	2.8	3.0	76	0.11	UC
SR6-08	20240281	1/2	0.78	19.8	400	2.8	4.0	102	0.16	UC
SR6-10	20240282	5/8	0.91	23.0	350	2.4	5.0	127	0.18	UC
SR6-12	20254775	3/4	1.05	26.6	300	2.1	6.0	152	0.25	UC

SR6

Low Pressure

Compatible Fittings

All fittings compatible with SR6 are listed in Section 5 (starting on page 246).

HOSE

