

Prospector™ Hot Oiler

This hose is designed for static-pressure, Hot Oiler applications. It is made specifically to handle the transfer of hot oil at 275°F continuous and 300°F intermittent to clear the paraffin around the casing to help start the flow of oil to the surface.



PERFORMANCE + SPECS

Meets flame resistance
USMSHA Designation

Inner Tube

Oil-resistant synthetic rubber

Reinforcement

Two braids of high-tensile steel wire

Cover

Black oil-resistant synthetic rubber

Temperature Range

-40°F to 275°F (-40°C to 135°C)

KEY FEATURES

~~LIFE™~~ Extended Life™ Cover

 Handles high temperature

 4:1 Safety Factor

BRANDING

 **Prospector™ X-Life HOT OILER** 1 ½" 2500 PSI Flame Resistant MSHA 2G-1C-14C/45

										
Part Number	SAP Number	Hose Size ID	in.	mm	psi	MPa	in.	mm	lbs./ft.	Fitting
Hot Oiler	20830012	1 ½	2.16	54.8	2500	17.2	20.0	508	1.64	B2

Prospector™ Hot Oiler
Special Application

Compatible Fittings

All fittings compatible with Prospector™ Hot Oiler are listed in Section 9 (starting on page 310).

HOSE

