

Saflex® (NSFX)

Saflex® NSFX is designed for medium-pressure applications where shock hazards exist and non-conductivity is required. This hose meets the maximum leakage of 100 microamps/ft. at 75 KV for 3 minutes.



PERFORMANCE + SPECS

Meets maximum leakage of **100 microamps/ft. at 75 KV** for 3 minutes

Inner Tube
CR (Polychloroprene)

Reinforcement

Two textile braids

Cover

Orange NBR/PVC (Nitrile/PVC)

Temperature Range

-40°F to 212°F (-40°C to 100°C)

KEY FEATURES



Non-conductive



4:1 Safety Factor

BRANDING

 **NSFX-08 Saflex® (Non-Conductive) 1/2" (12.7 MM) 2000 PSI (13.8 MPa)**

#	SAP	Hose Size ID	Hose OD	Max. Working Pressure		Min. Bend Radius		Weight	Fitting	
Part Number	SAP Number	in.	in.	mm	psi	MPa	in.	mm	lbs./ft.	
NSFX-04	20240283	1/4	0.56	14.2	2750	19.1	3.5	89	0.11	SF
NSFX-06	20240284	3/8	0.75	19.1	2250	15.5	4.0	102	0.19	SF
NSFX-08	20240285	1/2	0.94	23.7	2000	13.8	6.0	152	0.27	SF

HOSE



Saflex® (NSFX)

Special Application

Compatible Fittings

All fittings compatible with NSFX are listed in Section 10 (starting on page 368).