

SFS

SFS is made for medium-pressure hydraulic applications including fire suppression actuation equipment where the red cover allows for easy identification.



PERFORMANCE + SPECS

Meets flame resistance USMSHA Designation	Cover Red NBR/PVC (Nitrile/PVC)
Inner Tube NBR (Nitrile)	Temperature Range -40°F to 212°F (-40°C to 100°C)
Reinforcement One braid of high-tensile steel wire	

KEY FEATURES

- Flame-resistant
- 4:1 Safety Factor

BRANDING

SFS-08 Fire Suppression Hose **1/2" (DN12)** **2000 PSI**
13.8 MPa **MSHA 2G-1C-14C/31** **MADE IN USA**

										
Part Number	SAP Number	Hose Size ID	Hose OD	Max. Working Pressure	Min. Bend Radius	Weight	Fitting			
		in.	in.	mm	psi	MPa	in.	mm	lbs./ft.	
SFS-04	20276330	1/4	0.53	13.6	2750	19.1	4	102	0.15	B2
SFS-06	20276331	3/8	0.69	17.5	2250	15.5	5	127	0.22	B2
SFS-08	20276332	1/2	0.81	20.7	2000	13.8	7	178	0.28	B2
SFS-12	20276333	3/4	1.10	27.8	1250	8.6	9.5	241	0.41	B2
SFS-16	20276334	1	1.41	35.8	1000	6.9	12	305	0.62	B2

HOSE



SFS

Medium Pressure

Compatible Fittings

All fittings compatible with SFS are listed in Section 1 (starting on page 131).