



CHARGE AIR CONNECTOR (CAC)



COLD SIDE

This charge air connector for the cold side features 3-ply silicone coated polyester fabric with stainless steel pressure retention rings.

CONSTRUCTION:

+ Cold Side: 3-ply silicone coated polyester fabric with stainless steel pressure retention rings

SPECIFICATIONS:

+ Cold Side: wall thickness is .084"/.130"


BENEFITS

- ✓ Extreme Temperature Resistance
- ✓ Extreme Duty Cycle Tested for Hostile Engine Environments
- ✓ High Pressure Resistance

CUSTOM ENGINEERED TO WITHSTAND:



TEMPERATURE RANGE: COLD SIDE





CHARGE AIR CONNECTOR (CAC) – COLD SIDE

Part Number	Inside Diameter		Outside Diameter		Overall Length Inches	Convolutes (Humps)	Stainless Steel Rings	Max Operating Pressure - PSI	Weight LBS	Clamp
	Inch	MM	Inch	MM						
7758-0001	3.00	76	3.23	82	6.00	2	3	60	0.5	2583-0300 or 2584-0362
7753-0001	3.50	89	3.73	95	6.00	2	3	55	0.5	2583-0350 or 2584-0412
7755-0002	4.00	102	4.23	107	6.00	2	3	50	0.5	2583-0400 or 2584-0462
7759-0001	4.50	114	4.73	120	6.00	2	3	45	0.5	2583-0450 or 2584-0512

*Specifications for reference only. Specific test data available on request.