



CHARGE AIR CONNECTOR (CAC)

CONVOLUTED REDUCERS



Get great value with Flexfab's charge air convoluted (CAC) reducers. They can be used on both hot side and cold side of the CAC system and are constructed with 4-ply silicone coated meta-aramid fabric. Custom engineered to withstand harsh environments, they are resistant to extreme temperatures and pressures.

CONSTRUCTION:

+ 4-ply silicone coated meta-aramid fabric with stainless steel pressure retention rings where noted

SPECIFICATIONS:

+ Wall thickness is .092"/.132"


BENEFITS

- ✓ Can be Used on Both Hot Side and Cold Side of the CAC System
- ✓ Extreme Temperature Resistance
- ✓ Extreme Duty Cycle Tested for Hostile Engine Environments
- ✓ High Pressure Resistance

CUSTOM ENGINEERED TO WITHSTAND:



TEMPERATURE RANGE:



CHARGE AIR CONNECTOR (CAC) CONVOLUTED REDUCERS

Part Number	Inside Diameter		Outside Diameter		Overall Length Inches	Convoluters (Humps)	Stainless Steel Rings	Max Operating Pressure - PSI	Weight LBS	Clamp
	Inch	MM	Inch	MM						
7868	2.50/3.00	64/76	2.73/3.23	69/82	4.00	1	None	40	0.5	2583-0250/2583-0300 2584-0312/2584-0362
7726	3.00/3.50	76/89	3.23/3.73	82/95	5.00	1	2	55	0.5	2583-0300/2583-0350 2584-0362/2584-0412
7766	3.00/4.00	76/102	3.23/4.23	82/107	6.30	1	2	50	0.5	2583-0300/2583-0400 2584-0362/2584-0462
7880	3.50/4.00	89/102	3.73/4.23	95/107	6.00	2	2	50	0.5	2583-0350/2583-0400 2584-0412/2584-0462
7711	4.00/4.50	102/114	4.23/4.73	107/120	6.00	1	None	30	0.5	2583-0400/2583-0450 2584-0462/2584-0512
7866	4.00/4.50	102/114	4.23/4.73	107/120	7.00	2	3	45	0.6	2583-0400/2583-0450 2584-0462/2584-0512

*Specifications for reference only. Specific test data available on request.