



SUPERIOR PRODUCTS INTERNATIONAL II, INC.

Application Equipment (12/08)

The following is a guide. Changes in pressures and tip sizes may be needed for proper spray characteristics. Always purge spray equipment before use with reducer (acetone or MEK). Any reduction must be compatible with the existing environmental and application conditions. Refer to product application instructions for detailed application information.

Product Name:	Type of Equipment	Tip Size
Group 1:		
ENAMO GRIP	Airless	.011" - .015"
GRAFITTI CLEANER	Airless	.011" - .015"
INNER SEAL	Airless	.011" - .015"
ULTRACIDE	Airless	.011" - .015"
SP SEAL COAT	Airless	.011" - .015"
RUST GRIP	Airless	.011" - .015"

Group 2:

LINING KOTE	Airless	.017" - .021"
MOIST METAL GRIP	Airless	.017" - .021"
TOTAL SEAL	Airless	.017" - .021"

Group 3:

EPOXOTHERM*	Airless	.029" - .033"
SUNSHIELD 2000*	Airless	.029" - .033"
SUPERBASE(HS)*	Airless	.029" - .033"
SUPER THERM*	Airless	.029" - .033"
TOTAL SEAL (HS)	Airless	.029" - .033"
HSC	Airless	.035 (635)

Group 4:

SP2001F*	Texture Sprayer/Graco 833	3-4 mm nozzle/ 635
HOT PIPE COATING*	Texture Sprayer/Graco 833	3-4 mm nozzle/ 635

Group 5:

ACRYLIC STUCCO	Texture Sprayer	flexhead/pole spray
----------------	-----------------	---------------------

Equipment:

Group 1 &2:	Graco - (Model: 5900HD/ 7900HD 1.5 gal/min at 3000 psi)
Group 3:	Graco - (Model 7900HD 2.5 gal/min at 3000 psi)
Group 4:	Graco Texspray 1500 (RotoFlex or Carousel Style pumps at 2 gal/min at 100 psi) OR Graco 833
Group 5:	Graco TexSpray 1500 Use a Texture Flexhead and Pole



**SUPERIOR PRODUCTS
INTERNATIONAL II INC
USA**

*** Remove filters from spray equipment and spray guns before spraying coatings containing ceramics**