



MASTIC SEALING TAPE

Technical Data Sheet (06/09/06)

DESCRIPTION

MASTIC SEALING TAPE is a self-adhering, flexible membrane used to seal seams, cracks, and holes in surface to create an excellent substrate before applying acrylic coatings. MASTIC SEALING TAPE is a unique formulation of premium grade bituminous resin modified with synthetic resins. It is designed with an easy, peel-off paper backing to expose a highly adhesive bottom side and then placed over a clean, dry, and sound surface. The topside has a polyester mesh fabric built-in for strength and flexibility. MASTIC SEALING TAPE is inert and inorganic, and will never rot, decay, or be affected by bacteria or fungus. Available in 4 inch to 36 inch width rolls, 67 feet long.

TYPICAL USES

- ◆ As a fast and easy way to seal seams, cracks, and small holes
- ◆ Can be used on clean and dry concrete, wood, and steel.
- ◆ Excellent for bridging gaps on roofing to create a water-tight substrate for acrylic coatings.
- ◆ Used to seal seams in areas normally affected by bacteria or fungus.
- ◆ Used when ease and speed of application is urgent
- ◆ Can be used to seal steel buildings, grain bin bases, mobile home seams, air infiltration systems, foundations, decks, and many other substrates.

APPLICATION METHODS

MASTIC SEALING TAPE is to be applied to sound and dry surfaces. Surfaces must be free of dirt, oils, salts, and other debris before applying MASTIC SEALING TAPE. It will have excellent adhesion to many different substrates. Simply cut the length needed from the roll and peel off the paper backing. Lay the tape with the adhesive side down (mesh side up) over the area needing to be sealed. Be very cautious setting tape in place. The adhesive bottom-side is very strong and usually the MASTIC SEALING TAPE cannot be repositioned once it is laid into place. The tape should never be used alone since it is not U.V. stable and should remain clean and dry until it is over-coated with

Super Base/HS or Super Therm®. It is preferred that the tape not be coated during cooler temperatures until after being exposed to a few hours of sunlight to be sure the surface is warm enough.

PHYSICAL PROPERTY DATA

	UNIT	NOMINAL	TEST METHOD
Weight/100':	lbs.	24	
Thickness:		mils	40
Tensile:	P/S/I	256	ASTM D-882
Pliability:		Pass	ASTM D-146
Elongation:	%	58	ASTM D-882
Ultimate Failure of Tar Mass:	%	500	ASTM D-412

Property Values are Averages and Not Specifications Which Were Determined in Compliance with Test Methods.

AVAILABLE SIZES:

Roll Size	Rolls/Ctn	Weight/Ctn
24"x67'	1	38#
36"x67'	1	48#
4"x67'	9	54#
6"x67'	6	54#

These Items Sold in Full Cartons Only
Other Widths & Lengths Available on Special Order
Also Available:
Polyester Mesh - 4 roll - 36" x 360' (1080 sq.ft.)

SAFETY PRECAUTIONS

Do not use this product without first taking all appropriate safety measures to prevent property damage and injuries. **KEEP OUT OF REACH OF CHILDREN.**

LIMITATION OF LIABILITY: The information contained in this data sheet is based upon tests that we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by SPI, whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge is reliable. The products and information are designed for users having the requisite knowledge and industrial skills, and the end-user has the responsibility to determine the suitability of the product for its intended use.

SPI has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Therefore, SPI does not accept any liability arising from loss, injury, or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise).

The information contained in this data sheet is subject to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and the user has the responsibility to ensure that this sheet is current prior to using the product.