

LG REFRIGERATION

LRSES2706V

Super Capacity Side-By-Side Refrigerator with InstaView™ Door-in-Door®

- 27 cu.ft Large Capacity
- InstaView™ Door-in-Door®
- Sleek Design
- Fingerprint Resistant
- Ice Maker
- Multi Air Flow Cooling
- LED Lighting
- SmartDiagnosis™

AVAILABLE COLORS



Platinum Silver



CAPACITY	
Refrigerator (cu.ft.)	16.90
Freezer (cu.ft.)	9.90
Total Capacity (cu.ft.)	26.80
ENERGY	
Energy Consumption (kWh/Year)	673
ENERGY STAR® Qualified	DOE
WATER & ICE SYSTEM	
Daily Ice Production (lbs)	3.0 lbs
IcePlus™ Production (lbs)	3.5 lbs
Ice Storage Capacity (lbs)	6 lbs
Ice System	Factory Installed Ice Maker
COOLING	
Linear Compressor	Yes
Multi-Air Flow™ System	Yes
Temperature Sensors	4
CONVENIENCE	
Display Type	Membrane (White LED)
Temperature Controls	Electronic/Digital
Door Alarm	Yes
Child Lock	Yes
LoDecibel™ Quiet Operation	Yes
REFRIGERATOR	
No. of Shelves	4
Shelf Construction	Tempered Glass
Crisper Bins	2
Refrigerator Light	Ceiling LED
REFRIGERATOR DOOR	
InstaView™ Door-in-Door®	Yes
No. of Bins	9 Total (Including Door-in-Door®)
Door Bin Construction	1 Piece (clear)
FREEZER	
Door Type	Side Swing
Drawers/Shelves	2 Drawers/ 3 Shelves
Ice Bin / In-Door Ice	Icemaker & Ice bin in the freezer
Freezer Light	Ceiling LED
No. of Door Bins/Construction	4 / 1 Piece (clear)
Freezer Handle	Pocket Handle

Smart Features	
SmartDiagnosis™	Yes
MATERIALS AND FINISHES	
Contour Door	Yes
Hidden Hinges	Yes
Surface	Smooth
Fingerprint & Smudge Resistant Exterior	Yes
Handles	Pocket Handle
All Available Colors	Platinum Silver
DIMENSIONS/CLEARANCES/WEIGHTS	
Depth with Handles	34"
Depth without Handles	34"
Depth without Door	29 1/16"
Depth (Total with Door Open)	51 1/8"
Height to Top of Case	69 3/8"
Height to Top of Door Hinge	70 1/4"
Width	35 7/9"
Width (Door Open 90° with Handle)	44 1/5"
Width (Door Open 90° without Handle)	39 1/4"
Door Edge Clearance with Handle	3/8"
Door Edge Clearance without Handle	3/8"
Installation Clearance	Sides 1/8", Top 1", Back 2"
Weight (Unit/Carton)	284.4 lbs. / 293.2 lbs
Carton Dimensions (WxHxD)	38 1/2" x 72 1/4" x 37 31/64"
LIMITED WARRANTY	
Parts & Labor	1 Year
Sealed System (Parts & Labor)	5 Years
Compressor (Parts & Labor)	5 Years
Linear Compressor (Parts Only)	6-10 Years
UPC CODES	
LRSES2706V (Platinum Silver)	048231807234

LG REFRIGERATION

LRSES2706V

Super Capacity Side-By-Side Refrigerator with
InstaView™ Door-in-Door

QUICK INSTALL & CLEARANCES

For full installation directions/clearances please refer to the corresponding User Manual and Installation Guide.


DIMENSIONS/CLEARANCES/WEIGHTS

A Depth without Door	29 1/16"
B Depth with Handles	34"
C Depth without Handles	34"
D Depth (Total with Door Open 90°)	51 1/8"
E Width	35 7/9"
F Width (Door Open 90° with Handle)	44 1/5"
G Width (Door Open 90° without Handle)	39 1/4"
H Width (Door Open Fully)	FPO
I Door Edge Clearance with Handle (Not Shown)	3/8"
J Door Edge with Clearance without Handle (Not Shown)	3/8"
K Height to Top of Case	69 3/8"
L Height to Top of Door Hinge	70 1/4"
M Back Clearance	2"
N Front Clearance	24"
Installation Clearances	Sides 1/8", Top 1", Back 2"
Carton Dimensions (WxHxD)	38 1/2" x 72 1/4" x 37 31/64"

ENERGY


Energy Consumption (kWh/Year)	673
ENERGY STAR® Qualified	DOE

PRODUCT DIMENSIONS



CONNECTING POWER AND SECURING SPACE FOR WATER SUPPLY PIPE


- Make sure the location of the water supply pipe is within the marked range.
- Before connecting the power, always make sure to ground the product. (If the product is not grounded, the user may be able to feel the electricity due to the minute leakage current when touching the refrigerator door handle or side corner even when there is no issue with the product.)
- Do not ground the product to gas pipe, plastic water pipe or telephone wire etc. It can cause electric shock and explosion.



Power connection

The location of the 115V 60Hz power connector must be located on the rear side of the product as shown in the picture.

When installing the product, make sure to check whether the cord is hung on the hook on the rear side so that it is not pressed on the refrigerator. Damaged power cord can cause a fire.



Installation space for water supply pipe

Place the water hose for ice maker and water dispenser as shown in the picture, and prepare hose to come up from the floor. (Copper pipe with diameter of 5/16" (8mm) is recommended for the water hose.) If the water pipe and water hose is located far from the product, bury the water hose on the floor and provide appropriate treatment.

CHOOSING THE PROPER LOCATION

WATER

Select a place where a water supply can be easily connected for the automatic

NOTE

- The water pressure must be 20 – 120 psi or 138 – 827 kPa or 1.4 – 8.4 kgf/cm². If the refrigerator is installed in an area with low water pressure (below 20 psi), you can install a booster pump to compensate for the low pressure.

ELECTRICITY

The refrigerator should always be plugged into its own individual properly grounded electrical outlet rated for 115 Volts, 60 Hz, AC only, and fused at 15 or 20 amperes. This provides the best performance and also prevents overloading house wiring circuits which could cause a fire hazard from overheated wires. It is recommended that a separate circuit serving only this appliance be provided.

WARNING

- To reduce the risk of electric shock, do not install the refrigerator in a wet or damp area.

FLOORING

To avoid noise and vibration, the unit must be leveled and installed on a solidly constructed floor. If required, adjust the leveling legs to compensate for the unevenness of the floor. The front should be slightly higher than the rear to aid in door closing. Leveling legs can be turned easily by tipping the cabinet slightly. Turn the leveling legs to the left to raise the unit or to the right to lower it.

NOTE

- Installing on carpeting, soft tile surfaces, a platform or weakly supported structure is not recommended.

AMBIENT TEMPERATURE

Install this appliance in an area where the temperature is between 55°F (13°C) and 110°F (43°C). If the temperature around the appliance is too low or high, cooling ability may be adversely affected.

