

18" Monolith Wine




◀18▶

Available Accessories

- Stainless steel door panel
- Monolith brushed aluminum square handle
- Monolith stainless steel round handle
- Monolith brushed aluminum soft-edge handle
- Stainless steel Toe Kick
- Reverse door kit

See pages 42-43 for available accessories for single units and Side-by-Side combinations.


MW 1801

Infinity Light	Wine	Soft System	Smart Device	Telescopic Rails	
Sound rating dB(A)	38 *				
Total capacity cu.ft. (l)	8.2 (232)				
Max. No. of Bordeaux bottles (0.75l)	75				
Number of shelves	9				
Shelves on telescopic rails	9				
Shelf material	aluminum/ beech				
InfinityBoard	yes				
Electronic control	InfinitySwipe				
Temperature range °F (°C)	+41°F to +68°F (+5°C to +20°C)				
Temperature zones	2				
Temperature alarm	visual and acoustic				
Interior light	InfinityLight				
Door alarm	acoustic				
Safety thermostat	yes				
Activated Charcoal filter	yes				
Door type	insulated glass door				
Door hinges	left, reversible **				
Product dimensions					
in inch (H/W/D)	83 3/4" / 17 3/4" / 24"				
in cm (H/W/D)	212.6 / 45 / 61				
Cut out dimensions					
in inch (H/W/D)	84" / 18" / 25"				
in cm (H/W/D)	213.4 / 45.7 / 63.5				
Net weight lbs. (kg)	295.4 (134)				
Voltage V/Hz	115/60				
This unit is also available as MW 1800:				with right door hinges	

* Noise output – according to EN 60704-3.

** Please contact your Liebherr Authorized Dealer for door reversal.


Product Dimensions



IMPORTANT!

Stated minimum height dimensions include when the leveled feet are fully inserted.

Height can be increased by a maximum of 1" (26 mm) by turning the adjustable feet. When the appliance is fitted in the recess, the appliance must be raised by turning the adjustable feet so that the appliance top has contact with the anti-tipping bracket. This results in a 4" (102 mm) Toe Kick height.



Inset

A = 8 1/4" (210 mm)
B = 1 1/2" (12.5 mm)
C = 19 7/8" (505 mm)


Frameless

A = 8 1/2" (216 mm)
B = 1 1/2" (12.5 mm)
C = 20 3/8" (517 mm)


Dimension A = without mounted door handle

Cut out Dimensions

Continuous Toe Kick



Individual Toe Kick



A

Cabinet depth frameless installation style = 25" (635 mm)
Cabinet depth inset installation style = 25" (635 mm) + panel thickness

B

At this point the power cord exits from the appliance rear. 3/4" (19 mm) from the left and 5" (127 mm) from the floor. Free length of the power cord is 98" (2.5 m).

C

The appliance has a recess in this area for cable and waterline laying. 1" (25 mm) in depth and 5 1/2" (140 mm) in height over the whole width of the appliance.

D

This surface is visible when the appliance door is open. Designed finish is required.

E

The anti-tipping bracket is positioned at the base of the appliance and must be secured to the wall or to the floor, please refer to the installation manual for more information.

Door Panel Dimensions

and dimensions of free length for power


18" recess

Inset installation style


H = 79 7/8" (2029 mm) / h = 58 7/8" (1495 mm)
W = 17 3/4" (451 mm) / w = 11" (280 mm)

Frameless installation style

H = 80" (2032 mm) Add overlapping dimension to the panel on the top.
W = 18" (457 mm) Add overlapping dimension to the panel on both sides.



Panel thickness: Min. 5/8" (16 mm) * / Max. 1" (25.4 mm)
Panel and handle weight: Max. 52 lbs. (24 kg)



* If a shaker style panel is used, which is thinner than the minium panel thickness, shorter screws than those supplied in the accessory pack must be used.