


SIZE	STAINLESS	GREASE FILTER(S) (replacement)	NON-DUCTED FILTER(S)
30-in.	BPDP130SS	HPFA424 (Type "B5")	HPF24 (Type "Xb")
36-in.	BPDP136SS	HPFA430 (Type "C5")	HPF30 (Type "Xc")
42-in.	BPDP142SS	HPFA436 (Type "D5")	HPF36 (Type "Xd")
48-in.	BPDP148SS	HPFA442 (Type "E5")	HPF42 (Type "Xe")

PERFORMANCE								
Duct Orientation	Size	Damper	Sones		CFM @ 0.1 Ps			
Duct Orientation			Normal	High	Normal	High		
Vertical - Rectangular	3¼-in. x 10-in.	Included	0.3	6.5	120	360		
Horizontal - Rectangular	3¼-in. x 10-in.	Included	0.3	6.5	120	400		
Round - Vertical	7-in.	Sold Separately	0.5	6.5	120	370		

FEATURES				
Control type	2-speed Deluxe Rocker			
Delay off	no			
Filter Clean Reminder	no			
Heat Sentry™	no			
ADA Capable	yes			
Lighting	1-level LED (included)			
Grease Filter(s)	Hybrid Baffle (Qty. 2)			
Installation Hardware	EZ1 brackets			
ENERGY STAR®	no			
Recirculation	Non-ducted filter(s) sold separately			
AC INPUT				
120V, 60 Hz - 1.4 AMPS				
OPTIONAL ACCESSORIES				
7-in. Round Damper	BP87			
ADA Wiring Kit	HAWRK3			
Make-up Air Dampers	MD6TU, MD8TU and MD10TU			
MOUNTING HEIGHT				
18-in. to 30-in. from cooktop to bottom of hood				
LIMITED WARRANTY				
1-year				
3-year (LED modules only) (See installation manual for full warranty text.)				






HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-ofthe-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.



Under-Cabinet

SPIRE



99045757B

BPDP1 SERIES SPECIFICATION SHEET SPIRE