

Exclusive iQ Blower System™ with GPS Technology (see page 62) for the quietest, most energy efficient and fastest smoke and odor removal available in a range hood; choice of 13 Internal or External blower options offered separately.

Bright Halogen lighting floods the cooktop and surrounding area for clear visibility.

Mesh lined Hi-Flow™ baffle filters provide superior grease capture to ensure a clean, fresh kitchen.

Heat Sentry™ detects excessive heat and adjusts blower to high automatically.

Works with optional Universal Make-Up Air Dampers.

Model Numbers:



Rotary controls for two-level lighting and variable blower speeds enable the user to choose operating preferences.



Optional professional style backsplash with built-in holding racks.



Hi-Flow™ baffle filters utilize a V-mesh & baffle design to increase airflow, lower sound levels and provide excellent ventilation efficiency.



Hood Sizes

Remote Control

Non-ducted Capability

Filter Type

Widths	30", 36", 42", 48"
Depth	22"
Must purchase blower separately.	

Finish

Stocked	Brushed Stainless Steel
Special Order	Not Available
Features	
Lighting Type	Halogen, GU10, MR16, 50-watt
Number of Lamps	2 on 30", 36" 3 on 42", 48"
Lighting Levels	2
Lighting Lamps Included	Yes
Control Type	Variable Speed Rotary with Last Setting Memory
Control Features	Heat Sentry [™]

Not Available

Hi-Flow™ Baffle Filter

No Hood Blower Options (Must choose one blower sold separately)

Internal	iQ6	Р3	P5	P6	P8*
Blower CFM	600	300	500	600	900
Sones Low/High	0.3/7.5	0.3/3.5	10/10.5	2.0/9.5	10/10.5
External In-line	ILB3	ILB6	ILB9	ILB11	
Max CFM	280	600	800	1100	
Sone levels are typically half of comparable CFM internal blowers.					
External Exterior	EB6	EB9	EB12	EB15	
Max CFM	600	900	1200	1500	
Sone levels are typically half of comparable CFM internal blowers.					

^{*}P8 cannot be used with 30" width

Accessories


Backsplashes	RMP3004, RMP3604, RMP4204, RMP4804
	KIVIF40U4
II · I MIIA D	MD/TH MDOTH MD10TH

Universal MUA Damper MD6TU, MD8TU, MD10TU

Installation Requirements

zinotana troquir omionto	
Amps @ 120V	7.7 Max
Electrical Connection	Direct Wire
Duct Size: Internal Blower	8" (iQ6, P3, P6)
Duct Size: Internal Blower	3-1/4" x 10" (P5); x14" (P8)
Duct Size: External Blower	10" (at hood)
Duct Direction	Vertical & Horizontal (P5 & P8 only)
Backdraft Damper	Included





Installation height above the cooking surface: 24"-30"

For more details see the product specifications sheet found at www.BESTRangeHoods.com