

10-minute delay-off feature turns the hood off automatically.

Smooth stainless steel panel conceals mesh grease filters and enables increased flow around the perimeter for superior capture.

Works with optional Automatic Make-Up Air Dampers.

Model Numbers:



Powerful perimeter aspiration effectively removes heat, moisture and cooking aromas.



Variable 4-speed Electronic push-button control enables the user to choose operating preference.



Protect cabinetry from steam and grease with stainless steel liners that provide a custom fit.



Optional ACR2 remote control lets the busy cook stay in control from anywhere in the kitchen.



## Widths 21-3/16", 28-5/16" Depth 11-1/8" Finish Brushed Stainless Steel Stocked

| Otookou                 | Bradition Granifold Gradi                         |
|-------------------------|---|
| Features                |   |
| Lighting Type           | Halogen 20W, G-4                                  |
| Number of Lamps         | 2   |
| Lighting Levels         | 2*  |
| Lighting Lamps Included | Yes   |
| Control Type            | 4-speed Electronic Pushbutton,<br>Digital Display |
| Control Features        | Heat Sentry™, Delay Off,<br>Filter Clean Reminder |
| Remote Control          | Optional ACR2                                     |

Filter Type Mesh Grease Filters with Perimeter Aspiration Yes (P195P1 only) Non-ducted Capability

## Hood Blower Included (P195P)


| P6                     | P12                                      |  |
|------------------------|--|--|
| P195P1M52<br>P195P1M70 | P195P2M70                                |  |
| 600                    | 1200                                     |  |
|                        |  |  |
| 1.0/8.5                |  |  |
| 1.0/8.0                |  |  |
|                        | 2.0/12.0                                 |  |
|                        | P195P1M52<br>P195P1M70<br>600<br>1.0/8.5 |  |

## Accessories

**Hood Sizes** 

| 7 10000001100                    |                        |
|----------------------------------|------------------------|
| Non-Duct Filters                 | AFCP195P52, AFCP195P70 |
| Liners: Optional                 | L5230, L7036, L7048    |
| Light Panel for Liners: Optional | ALP30, 36, 48          |
| Make-Up Air Dampers              | MD6T, MD8T, MD10T      |
|                                  |                        |

| Installation Requirements  |   |
|----------------------------|---|
| Amps @ 120V                | 5.4 Max                                     |
| Electrical                 | Direct Wire                                 |
| Duct Size: Internal Blower | 6" for P1951M models<br>8" for P1952M model |
| Duct Size: External Blower | Not Available                               |
| Duct Direction             | Vertical                                    |
| Backdraft Damper           | Included                                    |



Installation height above the cooking surface: 24"-30"

For more details see the product specifications sheet found at www.BESTRangeHoods.com