

THERMOMASSEUR® BATH	\$
THERMASENS® BATH	\$
TUB	\$


THERMOMASSEUR (TMU)	
Jets	34
1 heated backrest	included
MiaMulti® Control*	included
Geysair [®]	included
AromaCloud [®]	\$
Chromatherapy - 2 LED	\$

THERMASENS (TMSU)	
AromaCloud®	included
Chromatherapy - 2 LED	included
WarmTouchShell®	included
DOT control	inst. & incl.

TUB
\$
\$
\$
included with therapy

FEATURES			
Installation		F	reestanding
No. of bathers	*	Imp. gallons	37
US gallons	44	Claw feet (specify finish)	included

OPTIONAL UPCHARGE APPLICABLE					
COLOR					
Standard		Option			\$
White Biscuit		Black	Sandbar	Gray	
Chrome Polished	Brushed nickel	Brass	Oil-rubbed bronze	Unplated	
FOR AIR SU	PPLY O	NLY			
Decorative pip	e (1 ½" x 6")			\$
Decorative pipe	e (1 1/2" x 24"	')			\$
Pipe concealer	(3" x 5 1/4")				\$
Elbow (45°)					\$
Elbow (90°)					\$
WASTE & O	ERFLO	N (EXP	OSED)		D13 (BALNEO®)
Chrome					\$
Brass			\$		
Brushed nickel	Brushed nickel, Polished nickel & Oil-rubbed bronze			\$	
Unplated			\$		
ISLAND TUB DRAINTM**					
Island Tub Drai	n™				\$







CELLA 6036 60" x 36" x 26"


ACCESSORIES (OPTIONAL) - There is a height difference for the rolled deck (see drawing Detail A). Faucets must be freestanding or wall-mounted. **OTHERS** - The turbine must be remotely installed. TMU: Control must be wall-mounted. TMSU: Dot controls are located on either sides of the AromaCloud.


TOTAL PRICE \$


FREESTANDING INSTALLATION











Available with flat or rolled deck.

Rolled deck

Detail A

LETTER	DESCRIPTION	MEASURE
A	Outside edge to center waste	11 1/4''
В	Outside edge to overflow	3 5/8"
С	Total length	60"
D	Total width	36"
E	Bathing well length	42 1/8"
F	Bathing well width	21 7/8"
G	Deck width	3 7/8"
Н	Flat surface width	2 1/2"
ı	Deck width	4"
J	Rolled deck width	3 7/8"
K	Height from bottom of lip to top deck	2 1/2"
L	Height from clawfoot to top of lip	27"
M	Height from clawfoot to top of lip	26"
N	Height from waste to center of overflow	15 5/8"
0	Maximum water level	13 7/8"
P	Slope of backrest	25°
Q	Length between clawfeet	34 3/4"
R	Width between clawfeet	22 3/4"
S	Distance from center air intake to center waste	5 1/2"
Т	Distance from center air intake to center waste	3"

Indicates heated backrest (TMU)

■ Indicates LED light position

☼ Indicates WarmTouchShell position (TMSU)
♠ Indicates AromaCloud position

TECHNICAL SPECIFICATIONS				
Hot water supply required	Should be 70% of water capacity of tub or greater.			
Turbine	Access to the pump must be at least 18" X 22". Standard connection is 20 A. 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option , a second line is needed 15 A. 120 V, 60 hz , dedicated line with a GFCI. Air vent necessary: 2" X 4" minimum			
Our products must be	installed by certified professionals only and according to our Owner's Manual as well as federal,			

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height.	
The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to	
change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ.	
BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.	

 $provincial/state\ and\ local\ building\ codes\ and\ regulations\ (www.bainultra.com/documentation).$

Approx. shipping weight	275 lbs
Turbine power	755 W
Air heater	700 W

WARRANTY	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

^{*}Some restrictions apply | www.bainultra.com/warranty



