

COMMERCIAL VINYL SERIES

Single Hung | Double Hung | Horizontal Slider | Fixed









Design Pressure Single Hung: up to 50 Double Hung: 35 Slider: 50 Fixed: up to 50	U-Value* Single Hung: .2552 Double Hung: .2451 Slider: .2552 Fixed: .2251
Air Infiltration Single Hung: <.30 Double Hung: <.30 Slider: <.30 Fixed: <.10	SHGC* Single Hung: .1262 Double Hung: .1162 Slider: .1262 Fixed: .1265
Water Resistance Single Hung: up to 7.5 Double Hung: 5.25 Slider: 7.5 Fixed: up to 7.5	* CR* Single Hung: 31 - 60 Double Hung: 31 - 59 Slider: 31 - 59 Fixed: 30 - 62
OITC× Single Hung: Contact Quaker Double Hung: Contact Quaker Slider: Contact Quaker	STC ^X Single Hung: Contact Quaker Double Hung: Contact Quaker Slider: Contact Quaker

Fixed:

► Integral nail fin

Mitered and welded corners

FEATURES:

applications 3/4" insulating glass

- ▶ Block & Tackle balancers in Hung models
- ▶ Brass rollers with stainless steel axle pins (Sliding model)

Commercial grade vinyl window for light commercial

- ▶ Steel reinforcements added throughout for additional strength
- ► Numerous mull systems for multi-unit combos
- ► White or Sandstone vinyl
- Optional painted exterior (meets FGIA 615 finish)
- Textured laminate options for exterior and interior
- Use up to 4 floors with standard fin-install. Up to 6 stories with sill pan or receptor/subsill installation accessories

Contact Quaker

Fixed:

Contact Quaker

^{*-}Ranges based on multiple Low-E/Argon I.G. combinations

X-Ranges based on multiple I.G. combinations



V250 COMMERCIAL VINYL SERIES

Single Hung (LC35)

Test size = 36" x 84"

Double Hung (LC35)

Test size = 36" x 84"

27"


28"

3"


4"

8"

Fixed (LC35)



Horizontal Slider (LC35)



All ratings listed are NAFS certified.



QuakerCommercialWindows.com 1-800-347-0438 Commercial@quakerwindows.com