

### Single Hung | Double Hung | Fixed









Design Pressure Hung: 40 Fixed: 50	U-Value* Hung: .3656 Fixed: .2550
Air Infiltration Hung: <.30 Fixed: <.10	SHGC* Hung: .1356 Fixed: .1669
Water Resistance Hung: 8.15 Fixed: 10	* CR* Hung: 41 - 51 Fixed: 42 - 58
OITC <sup>X</sup> Hung: Contact Quaker  Fixed: Contact Quaker	STC <sup>X</sup> Hung: Contact Quaker Fixed: Contact Quaker

\*-Ranges based on multiple Low-E/Argon I.G. combinations

x-Ranges based on multiple I.G. combinations

#### **FEATURES:**

- ► Architectural grade aluminum frame
- ► Thermally-broken frame and sash with pourand-debridge technology
- ▶ 1" insulating glass
- Dual locking systems on Double Hung model with gravity locks on bottom sash and swivel locks at the meeting rail
- Gravity lock hardware on bottom sash of Single Hung models
- ▶ Block & Tackle balance system
- ► Tilt-in sash system with stainless steel pivot pins
- 30+ "Quick-Pick" colors, with unlimited custom colors available
- Standard High-Performance 2604 Powder Paint Finish (an FGIA Specification)
- ▶ Optional Upgrade to 2605 Powder Paint Finish (an FGIA Specification)
- ► Extruded aluminum screen





## E500

#### E500 Series Hung (AW40)

# 

#### E500 Fixed (AW50/CW70)







QuakerCommercialWindows.com 1-800-347-0438 Commercial@quakerwindows.com