

Payanywhere Smart POS

Specifications | PAX E500



Software	The PayAnywhere Application
Operating System	PayDroid based on Android 6.0
Q20 Module	PCI PTS 5.x Certified Payment Terminal 4.3 Inch Color Capacitive Touch Screen
Processor	Quad-Core Cortex A53, 1.2GHZ
Memory	1GB RAM + 8GB FLASH
Display	8 Inch all Perspective-IPS Screen, 1280 x 800 Pixels HD Display Capacitive Touch Screen
Communication	WiFi: 802.11 b/g/n, 2.4G, Supports Hot Spot and WiFi probe Bluetooth: BLE 4.0 3G / 4G (optional)
Audio	2 Stereo Speakers - 4Ω / 2W
Physical	L x W x H (in): 7.9 x 9.6 x 11.6 L x W x H (cm): 20 X 24.3 x 29.5 Weight (lb): 11 Weight (kg): 5
Printer	3 Inch Thermal Printer Head Automatic Paper Receipt Cutter Paper Width: 80mm Diameter: 80mm
Peripheral Ports	1 SIM Card Slot 1 Micro SD Card Slot, Supports up to 32GB 1 x Cash Box RJ11 (24V) 2 x RS232 2 x USB HOST2.0 1 x Micro USB OTG2.0 1 x HDMI1.4 Type A 1 x Audio Jack 2 x LAN
Voltage	Input: 100 - 240V AC, 50Hz / 60Hz Output: 24V / 2.7A
Cameras	5 Megapixel Rear Auto Zoom Camera for 1D & 2D Code Scanning 2 Megapixel Front Fixed Focal Camera
Battery	Li-Ion Battery, 2600mAh, 3.7V
Physical Keys	1 x ON/OFF Key 1 x Printer Paper Button 1 x Volume +/- Key 1 x Custom Shortcuts
Indicator	Printer Power Indicator (green) Printer Paper Out Indicator(yellow) Printer Error Indicator (red) Charge Indicator (red) Information Indicators (blue)
Certifications	PCI PTS 5.x EMV L1 & L2 Mastercard Contactless Visa Visa payWave Amex Expresspay Discover D-PAS Mastercard TQM NSICC