



Billing Code 4910-13

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 25

[Docket No. FAA-2019-0235; Special Conditions No. 25-747-SC]

Special Conditions: Airbus Model A330 Series Airplanes; Seats with Inertia Locking Devices

AGENCY: Federal Aviation Administration (FAA), DOT.

ACTION: Final special conditions.

SUMMARY: These special conditions are issued for the Airbus Model A330 series airplane. These airplanes will have a novel or unusual design feature when compared to the state of technology envisioned in the airworthiness standards for transport-category airplanes. This design feature is seats with inertia locking devices. The applicable airworthiness regulations do not contain adequate or appropriate safety standards for this design feature. These special conditions contain the additional safety standards that the Administrator considers necessary to establish a level of safety equivalent to that established by the existing airworthiness standards.

DATES: Effective [INSERT DATE OF PUBLICATION IN THE FEDERAL REGISTER].

FOR FURTHER INFORMATION CONTACT: Shannon Lennon, Cabin and Airframe Safety Section, AIR-675, Transport Standards Branch, Policy and Innovation Division, Aircraft Certification Service, Federal Aviation Administration, 2200 South 216th Street, Des Moines, Washington 98198; telephone and fax 206-231-3209; e-mail shannon.lennon@faa.gov.

SUPPLEMENTARY INFORMATION:

Background

On February 13, 2019, Airbus applied for a change to Type Certificate No. A46NM for seats with inertia locking devices in Model A330 series airplanes. The Model A330 series

airplane is a twin-engine, transport-category airplane with a maximum takeoff weight of 533,518 pounds and seating for 440 passengers.

Type Certification Basis

Under the provisions of title 14, Code of Federal Regulations (14 CFR) 21.101, Airbus must show that the Model A330 series airplanes, as changed, continue to meet the applicable provisions of the regulations listed in Type Certificate No. A46NM, or the applicable regulations in effect on the date of application for the change, except for earlier amendments as agreed upon by the FAA.

If the Administrator finds that the applicable airworthiness regulations (i.e., 14 CFR part 25) do not contain adequate or appropriate safety standards for Airbus Model A330 series airplanes because of a novel or unusual design feature, special conditions are prescribed under the provisions of § 21.16.

Special conditions are initially applicable to the model for which they are issued. Should the type certificate for that model be amended later to include any other model that incorporates the same novel or unusual design feature, or should any other model already included on the same type certificate be modified to incorporate the same novel or unusual design feature, these special conditions would also apply to the other model under § 21.101.

In addition to the applicable airworthiness regulations and special conditions, Airbus Model A330 series airplanes must comply with the fuel-vent and exhaust-emission requirements of 14 CFR part 34, and the noise-certification requirements of 14 CFR part 36.

The FAA issues special conditions, as defined in 14 CFR 11.19, in accordance with § 11.38, and they become part of the type certification basis under § 21.101.

Novel or Unusual Design Features

Airbus Model A330 series airplanes will incorporate the following novel or unusual design features:

Seats with inertia locking devices (ILD).

Discussion

Airbus will install, in Model A330 series airplanes, Thompson Aero Seating Ltd. passenger seats that can be translated in the fore and aft direction by an electrically powered motor (actuator) that is attached to the seat primary structure. Under typical service-loading conditions, the motor internal brake is able to translate the seat and hold the seat in the translated position. However, under the inertial loads of emergency-landing loading conditions specified in 14 CFR 25.562, the motor internal brake may not be able to maintain the seat in the required position. The ILD is an “active” device intended to control seat movement (i.e., a system that mechanically deploys during an impact event) to lock the gears of the motor assembly in place. The ILD mechanism is activated by the higher inertial load factors that could occur during an emergency landing event. Each seat place incorporates two ILDs, one on either side of the seat pan. Only one ILD is required to hold an occupied seat in position during worst-case dynamic loading specified in § 25.562.

The ILD will self-activate only in the event of a predetermined airplane loading condition such as that occurring during crash or emergency landing, and will prevent excessive seat forward translation. A minimum level of protection must be provided if the seat-locking device does not deploy.

The normal means of satisfying the structural and occupant protection requirements of § 25.562 result in a non-quantified, but nominally predictable, progressive structural deformation or reduction of injury severity for impact conditions less than the maximum specified by the rule.

A seat using ILD technology, however, may involve a step change in protection for impacts below and above that at which the ILD activates and deploys to retain the seat pan in place. This could result in structural deformation or occupant injury output being higher at an intermediate impact condition than that resulting from the maximum impact condition. It is acceptable for such step-change characteristics to exist, provided the resulting output does not exceed the maximum allowable criteria at any condition at which the ILD does or does not deploy, up to the maximum severity pulse specified by the requirements.

The ideal triangular maximum severity pulse is defined in Advisory Circular (AC) 25.561-1B. For the evaluation and testing of less-severe pulses for purposes of assessing the effectiveness of the ILD deployment setting, a similar triangular pulse should be used with acceleration, rise time, and velocity change scaled accordingly. The magnitude of the required pulse should not deviate below the ideal pulse by more than 0.5g until $1.33 t_1$ is reached, where t_1 represents the time interval between 0 and t_1 on the referenced pulse shape as shown in AC 25.561-1B. This is an acceptable method of compliance to the test requirements of the special conditions.

Conditions 1 through 5 address ensuring that the ILD activates when intended, to provide the necessary protection of occupants. This includes protection of a range of occupants under various accident conditions. Conditions 6 through 10 address maintenance and reliability of the ILD, including any outside influences on the mechanism, to ensure it functions as intended.

These special conditions contain the additional safety standards that the Administrator considers necessary to establish a level of safety equivalent to that established by the existing airworthiness standards.

Discussion of Comments

The FAA issued Notice of Proposed Special Conditions No. 25-19-02-SC for the Airbus Model A330 series airplane. This document was published in the *Federal Register* on April 16, 2019 (84 FR 15531). No comments were received, and the special conditions are adopted as proposed.

Applicability

As discussed above, these special conditions are applicable to Airbus Model A330 series airplanes. Should Airbus apply at a later date for a change to the type certificate to include another model incorporating the same novel or unusual design feature, these special conditions would apply to that model as well.

Conclusion

This action affects only one novel or unusual design feature on one model series of airplanes. It is not a rule of general applicability.

List of Subjects in 14 CFR Part 25

Aircraft, Aviation safety, Reporting and recordkeeping requirements.

Authority Citation

The authority citation for these special conditions is as follows:

Authority: 49 U.S.C. 106(f), 106(g), 40113, 44701, 44702, 44704.

The Special Conditions

Accordingly, pursuant to the authority delegated to me by the Administrator, the following special conditions are issued as part of the type certification basis for Airbus Model A330 series airplanes.

In addition to the requirements of § 25.562, passenger seats incorporating inertia locking devices (ILD)s must meet the following:

1. **Level of Protection Provided by ILD** — It must be demonstrated by test that the seats and attachments, when subject to the emergency-landing dynamic conditions specified in § 25.562, and with one ILD not deployed, do not experience structural failure that could result in:
 - a. Separation of the seat from the airplane floor.
 - b. Separation of any part of the seat that could form a hazard to the seat occupant or any other airplane occupant.
 - c. Failure of the occupant restraint or any other condition that could result in the occupant separating from the seat.
2. **Protection Provided Below and Above the ILD Actuation Condition** — If step-change effects on occupant protection exist for impacts below and above that at which the ILD deploys, tests must be performed to demonstrate that the occupant is shown to be protected at any condition at which the ILD does or does not deploy, up to the maximum severity pulse specified by § 25.562. Test conditions must take into account any necessary tolerances for deployment.
3. **Protection Over a Range of Crash Pulse Vectors** — The ILD must be shown to function as intended for all test vectors specified in § 25.562.
4. **Protection During Secondary Impacts** — The ILD activation setting must be demonstrated to maximize the probability of the protection being available when needed, considering a secondary impact that is above the severity at which the device is intended to deploy up to the impact loading required by § 25.562.
5. **Protection of Occupants other than 50th Percentile** — Protection of occupants for a range of stature from a two-year-old child to a ninety-five percentile male must be shown.

6. **Inadvertent Operation** — It must be shown that any inadvertent operation of the ILD does not affect the performance of the device during a subsequent emergency landing.
7. **Installation Protection** — It must be shown that the ILD installation is protected from contamination and interference from foreign objects.
8. **Reliability** — The performance of the ILD must not be altered by the effects of wear, manufacturing tolerances, aging or drying of lubricants, and corrosion.
9. **Maintenance and Functional Checks** — The design, installation, and operation of the ILD must be such that it is possible to functionally check the device in place.

Additionally, a functional-check method and a maintenance-check interval must be included in the seat installer's instructions for continued airworthiness (ICA) document.
10. **Release Function** — If a means exists to release an inadvertently activated ILD, the release means must not introduce additional hidden failures that would prevent the ILD from functioning properly.

Issued in Des Moines, Washington, on May 22, 2019.

Victor Wicklund,
Manager, Transport Standards Branch,
Policy and Innovation Division,
Aircraft Certification Service.
[FR Doc. 2019-11071 Filed: 5/28/2019 8:45 am; Publication Date: 5/29/2019]