

STAINLESS STEEL SPRINKLER UTILITY PUMP

APPLICATIONS

Ideal for pressure boosting, sprinkler systems, and general purpose applications where portability and corrosion-resistance is important.

FEATURES & BENEFITS

- **Self-priming utility pump**
Designed to lift water up to 25'
- **Corrosion-resistant stainless steel pump housing**
Ideal for operating lawn sprinklers, pressure boosting, and other general purpose applications
- **Heavy-duty 3/4 hp 115 Volt motor**
For years of service and reliability
- **Glass-filled thermoplastic impeller and diffuser**
For high performance and efficient water flow
- **Power cord, carry handle, and garden hose adapter included**
For convenience and portability



| Model | Item Number | UPC | HP | Volts | Amps | Cord Length | Intake | Discharge | Discharge Pressure PSI at 5' Lift | | | | | Max. Flow at 5' Suction Lift | Max. Pressure PSI | Max. Head FT |
|-----------|-------------|-----------------|-----|-------|-------|-------------|--------|-----------|-----------------------------------|-----|-----|-----|-----|------------------------------|-------------------|--------------|
| | | | | | | | | | 20 | 30 | 40 | 50 | 60 | | | |
| | | | | | | | | | Gallons Per Minute | | | | | | | |
| RJSE-75SS | 614432 | 0 10121 14415 6 | 3/4 | 115 | 7.0 A | 8' | 1" | 1" FNPT | 13.9 | 8.5 | 5.3 | 2.5 | 0.3 | 17 GPM | 64 | 147 |

Carton Specifications

| Model | Length | Width | Height | Weight (lbs) | Carton Cubes (cu ft) | Pallet Quantity | Qty. per Layer | Layers per Pallet |
|-----------|--------|--------|--------|--------------|----------------------|-----------------|----------------|-------------------|
| RJSE-75SS | 8.33" | 14.33" | 10" | 21 | 0.69 | 48 | 12 | 4 |

Stainless Steel Sprinkler Utility Pump

