

Classic Flame Pro Specification Comparison Chart

All products meet or exceed the standard for CSA and UL Certification and have been extensively tested in Twin Star International, Inc. factory.



MPN	Type	Trim Kit	Flame Type	Style	Fuel Bed	Wiring	Volts	BTUs	Watts	Heater	Heats	Amps	W	D	H	Product
25EF031GRP	Plug In	N/A	SpectraFire	Traditional	Logs	Plug-In	120	4600	1350	Fan Forced Air	400	12	27	11.2	17.7	View Details
25II310GRA	Plug In	N/A	SpectraFire	Traditional	Logs	Plug-In	120	5200	1500	Infrared	1000	12.5	27	11.2	17.7	View Details
32II310GRA	Plug In	N/A	SpectraFire	Traditional	Logs	Plug-In	120	5200	1,500	Infrared	1000	12.5	34.1	12.2	20.6	View Details
23EF031GRP	Plug In	BBKIT-23	SpectraFire	Traditional	Logs	Plug-In	120	4600	1,350	Fan Forced Air	400	12	27.32	9.28	24.28	View Details
23II310GRA	Plug In	BBKIT-23	SpectraFire	Traditional	Logs	Plug-In	120	5200	1,500	Infrared	1000	12	27.32	9.28	24.48	View Details
26EF031GPG-201	Plug In	BBKIT-26	SpectraFire	Contemporary	Glass	Plug-In	120	4600	1,350	Fan Forced Air	400	12	30.71	9.5	21.89	View Details
26EF031GRP	Plug In	BBKIT-26	SpectraFire	Traditional	Logs	Plug-In	120	4600	1,350	Fan Forced Air	400	12	30.71	9.5	21.89	View Details
26II310GRA	Plug In	BBKIT-26	SpectraFire	Traditional	Logs	Plug-In	120	5200	1500	Infrared	1000	12.5	30.71	9.5	21.89	View Details
26II310GRG-201	Plug In	BBKIT-26	SpectraFire	Traditional	Logs	Plug-In	120	5200	1500	Infrared	1000	12.5	30.71	9.5	21.89	View Details
28II300GRA	Plug In	BBKIT-28	SpectraFire	Traditional	Logs	Plug-In	120	5200	1500	Infrared	1000	12.5	32.91	10.35	27.21	View Details
33II310GRA	Plug In	BBKIT-33	SpectraFire	Traditional	Logs	Plug-In	120	5200	1500	Infrared	1000	12.5	37.72	10.35	30.3	View Details
36EB110-GRT	Builder's Box	Self Trimming	Standard	Traditional	Logs	Direct-Wire or Plug Kit	120	4400	1,440	Fan Forced Air	400	12	36	7.62	24	View Details
36EB111-GRC	Builder's Box	Self Trimming	Standard	Contemporary	Rocks	Direct-Wire or Plug Kit	120	4400	1,440	Fan Forced Air	400	12	36	7.62	24	View Details
36EB220-GRT	Builder's Box	Self Trimming	Standard	Traditional	Logs	Direct-Wire	220	8900	2800	Fan Forced Air	800	11.7	36	7.625	24	View Details
36EB221-GRC	Builder's Box	Self Trimming	Standard	Contemporary	Rocks	Direct-Wire	240	8900	2800	Fan Forced Air	800	11.7	36	7.62	24	View Details
39EB500GRA (Fixed Glass)	Builder's Box	Self Trimming	Standard	Traditional	Logs	Direct-Wire or Optional Plug Kit	120 208 240	4915 7170 9560	1440 2100 2800	Fan Forced Air	400 800 800	12 10.1 11.7	38.9	15.66	32.4	View Details
39EB500GRS (Swinging Doors)	Builder's Box	Self Trimming	Standard	Traditional	Logs	Direct-Wire or Optional Plug Kit	120 208 240	4915 7170 9560	1440 2100 2800	Fan Forced Air	400 800 800	12 10.1 11.7	38.9	15.66	32.4	View Details