

Recessed MR16 Spot RSPOT-CB



NTD's Recessed Spot is designed for both down light applications under soffit or as an inground spot. Veratile and durable, constructed of cast brass with a weathered brass finish. Includes cast brass grate as well as a Beryllium pre-greased socket

SPECIFICATIONS:

• Voltage: 12VOLT

• Construction: Cast Brass

• Weight: 2.41 lbs.

• Finish: Weathered Brass

• Mounting: Recessed Mount or Inground w/ sleeve (included)

Lamp: LED or Halogen MR16Wattage: Maximum 35 Watts

• Wire: 25' Lead 18/2

• Sockets: Beryllium Copper Pre-Greased Socket

• Lens: Clear Convex Tempered Glass

$\begin{array}{c} \textbf{Dimensions} \\ 3.9 \times 4.0 \end{array}$

Lamp Options MR16 LED MR16 Incandescent

Mount Options

Recessed Mount Inground

Lens Options

Clear Glass: normal light output (standard)
Frosted Glass: reduce/soften light output
Dimpled: spread light outward
Linear: focus beam to a long narrow pattern
Hex Louver: honeycomb/ reduced glare

	PROJECT DETAILS
Quantity	
Lamp	
Mount	
Lens	
Riser	
Notes	

