

4-Channel WiFi NVR Specifications		
Video/Audio Input	IP Video Input	4CH
	Audio Input	Support the IP Camera Audio Input
Video/Audio Output	HDMI Output	1CH, Resolution: 1920*1080, 1440*900, 1280*1024, 1280*800, 1280*720, 1024*768
	VGA Output	1CH, Resolution: 1920*1080, 1440*900, 1280*1024, 1280*800, 1280*720, 1024*768
	Audio Output	1CH, RCA
Decoding	Video Format	H.264
	Live View/Playback Resolution	1080p/720p
	Frame Rate	720p: 4CH@25fps, 1080p: 4CH@15fps
	Synchronous Playback	4CH@1080p
HDD	SATA Devices	1 x SATA HDD
	Dimension	2.5", 3.5"
	Maximum Capacity	8TB (Maximum 4TB HDD/Port)
External Interface	USB Interface	2 x USB 2.0
	Network Interface	1CH RJ45, 10M/100M Ethernet
Wireless Routing	Wireless Standard	IEEE 802.11b/g/n
	Operating Frequency	2.4 GHz
	Wireless Security	WPA2-PSK (AES)
Network	Network Protocol	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, SMTP, SSL/TLS, DNS, NTP
	Browser Supported	IE
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Max. User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams).
General	Power Supply	DC 12V/2A
	Power Consumption	<5W (Without HDD)
	Working Environment	-10°C~+55°C (14°F~131°F), Humidity: 10%~90%
	Dimension	260x41x230 mm
	Weight (Without HDD)	1.0 kg

RLC-210W Specifications		
Camera	Image Sensor	1/2.7" CMOS Sensor
	Effective Pixels	1920x1080 (2.0 Megapixels)
	Lens	f=4.0 mm Fixed, F=2.0
	Angle of View	Horizontal: 90°, Vertical: 46°
	Day/Night Mode	Auto Switchover
	Min. Illumination	0 Lux (With IR Illuminator)
	IR Distance	30 Meters (100ft)
	Backlight Compensation	Support
	Noise Reduction	3D DNR
Video	Compression	H.264
	Resolution	Mainstream: 1080p, 720p; Substream: 640 x 360
	Bitrate	Mainstream: 256Kbps~3072Kbps; Substream: 64Kbps~512Kbps
	Frame Rate	PAL/NTSC: Mainstream@15fps, Substream@15fps
Audio	Compression	AAC
	Interface	Built-in Microphone
Network	Interface	One 10M/100Mbps RJ45
	Network Protocol	No
	Browser Supported	No
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Max. User Access	12 Users; Support up to 12 simultaneous video streams (10 substreams and 2 mainstreams).
WiFi	Wireless Standard	IEEE 802.11a/b/g/n
	Operating Frequency	2.4 GHz/5 GHz
	Wireless Security	WPA-PSK/WPA2-PSK
General	Power Supply	DC 12V
	Power Consumption	<8W
	Working Environment	-10°C~+55°C (14°F~131°F), Humidity: 10%~90%
	Ingress Protection	IP66
	Dimensions	Φ70*196 mm
	Weight	450 g