

**Self Latching Flush Bolt With Bottom Fire Bolt  
(for Fire Rated Metal Doors)  
No. 1849**



- Material:** Brass, Stainless Steel
- Finishes:** US3, US4, US10, US10B, US26, US26D, US32D
- Fastener:** 8 ea. #8 x 3/4 FH Combo Screws, 4 ea. Plastic Anchors
- Features:**
- Non-handed.
  - Low (5 lbs. maximum) closing force.
  - Self latching top bolt.
  - Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike.
  - Bolt head rod is adjustable up to 1 1/2".
  - For fire rated metal doors labeled A, B, C, D, & E up to 4'w x 10'h.
  - Thermal lock automatically locks the inactive door under high heat conditions due to fire.
  - Bottom fire bolt eliminates need for floor prep.
  - Oversize fire bolt strike hole allows for slight door misalignment.

No.	Size	Weight
1849	<b>Top Bolt:</b> 1" x 6 3/4" <b>Bottom Bolt:</b> 13/16" dia.	1.3 lbs.

**Self Latching Flush Bolt With Bottom Fire Bolt  
(for Fire Rated Wood Doors)  
No. 1949**



- Material:** Brass, Stainless Steel
- Finishes:** US3, US4, US10, US10B, US26, US26D, US32D
- Fastener:** 6 ea. #8 x 3/4 FH Combo Screws, 2 ea. Plastic Anchors; 3 ea. #10 x 1 FH WS
- Features:**
- Non-handed.
  - Low (5 lbs. maximum) closing force.
  - Self latching top bolt.
  - Override feature prevents damage to doors or bolt if bolt head is blocked from entering strike.
  - Bolt head rod is adjustable up to 1/2".
  - For fire rated UL listed 20-minute wood core and composite doors up to 4'w x 9'h.
  - Thermal lock automatically locks the inactive door under high heat conditions due to fire.
  - Bottom fire bolt eliminates need for floor prep.
  - Oversize fire bolt strike hole allows for slight door misalignment.

No.	Size	Weight
1949	<b>Top Bolt:</b> 1" x 8 1/2" <b>Bottom Bolt:</b> 13/16" dia.	1.6 lbs.