

ALL SHOPS

FIRE RATED DOOR

<20.5'

SS MOUNTING BRACKET LOOSE

MECHANICAL INTERLOCK INCLUDED -

SS LATCH
COVER

— SS PADDLE
LATCH
AS07478

— SPRING LOAD
SS HINGE

FLAT BAR STIFFENER

REVISIONS				MATERIAL SPEC. 304SS SD-PVC	FINISH SPEC. ELECTROPOISHED	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES		 Terra Universal Proprietary & Confidential All rights reserved by TERRA UNIVERSAL Disclosure or Copying Prohibited	TITLE	
R#	DESCRIPTION	DATE	BY			TOLERANCES ON:			Pass-Through, Fire Rated Door	
NC	INITIAL RELEASE	01-14-15	BL			.XX DECIMALS ± .03	X' ± 1"		304SS Clear Seam, 18 Wx20.5 Dx24 H	
○						.XXX DECIMALS ± .010	X/Y ± 1/64		ELECTROPOISHED	
						SIGNATURES			DATE	
						ISSUED BY: BRYAN LE			8/26/2016	
				REF #	P100615			A 1993-72A		
								SCALE	SHEET 1 OF 13	