

**160/40**

(GB)

- Resettable PIN
- Hardened steel shackle
- Shackle diameter 6.0 mm

(FR)


- Combinaison programmable
- Anse en acier cémenté
- Diamètre anse 6,0 mm

(ES)


- PIN resetable
- Arco de acero endurecido
- Diámetro del arco 6,0 mm

(PT)

- Código ajustável
- Arco de aço endurecido
- Diâmetro do arco 6,0 mm



a = 42,0 mm  
b = 24,0 mm  
c = 22,0 mm  
d = 6,0 mm



**Features - Caractéristiques - Características - Características**



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



**ADVERTENCIA:** Cáncer y Daño Reproductivo - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



**AVERTISSEMENT:** Cancer et Troubles de l'appareil reproducteur - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**AVISO:** Câncer e danos Reprodutivos - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

(GB) Shackle made from hardened steel

(FR) Anse en acier cémenté

(ES) Arco hecho de acero endurecido

(PT) Arco feito de aço endurecido

**Applications - Utilisation - Aplicaciones - Aplicações**



**160/40 B/EFSP**

**1 14Z331**



[www.abus.com](http://www.abus.com)



0 78217 12611 0

331956