

RD-5090

DUCT DOORS for round ducts

Application

- Economical access to round ducts

Product Features

- Pull and catch lock system
- Gasketing on the door assures a tight seal without obstruction in the air system

RD-5090 Duct Access Door Specifications:

Door / Door Frame: 16 gauge galvanized steel

Gasketing: 1/8" thick by 1" wide closed cell neoprene

Standard Latch: Plated steel pull and catch

Finish: Mill / Aluminum

RD-5090 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Opening	Weight per Door	
Inches	mm		lbs.	kg.
6 x 4	150 x 100	5"	1	0.5
7 x 5	175 x 125	6"	1.25	0.6
8 x 6	200 x 150	7"	1.5	0.7
9 x 8	225 x 200	8"	1.75	0.8
10 x 8	250 x 200	9"	2	0.9
11 x 9	275 x 225	10"	3	1.2
13 x 10	325 x 250	12"	3.5	1.6
15 x 13	375 x 325	14"	4	1.8
17 x 13	425 x 325	16"	5.5	2.5
19 x 15	475 x 375	18"	6	2.7
19 x 17	475 x 425	20"	6.75	3.1
20 x 17	500 x 425	24"	7.25	3.3

Duct opening is normal door size plus +3/8" (9mm)

For detailed specifications see submittal sheet

