
HOLLOW METAL FRAME

Two Rows of Inverted Split "Y" Blades in a 1-13/16" Frame for Flush Mounting in Hollow Metal Frames.



SPECIFICATIONS:

Material:	18 gauge CRS. Min size 6" x 4", Max 36" x 36". Multiple sections can be combined for larger sizes		
Construction	2 rows of inverted split "Y" blades at 1" intervals. Blades are attached by interlocking construction to the 1-13/16" deep assembly mounted in a "U" channel frame. Non-vision Construction. Multiple sections can be combined for larger transoms.		
Frame:	For installation into hollow metal frame by others. Frame inside dimensions of opening = order size. Mounting clips furnished with hex head self-drilling tek screw.		
Fasteners:			
Powder Coat Finishes:	(BK) Black(FBK) Flat Black(W) White(SB) SC Beige(SI) Silver(R) Red(S) Sand(AB) AMS Beige(GH) Gray Hammertone Color Samples Online		
Free Flow Are	50% free area.		

OPTIONAL FEATURES AT AN ADDITIONAL COST:

Finishes & Materials:	(S) 20 gauge #4 stainless steel satin finish 16 gauge CRS (J) Galvanneal sheet for exterior use and corrosion-resistance (E) Electro Galvanized for corrosion resistance & exterior use	
Screen:	18x14 mesh insect screen installed with rivets or screws aluminum bronzefiberglass stainless Bird Screen.	
Custom:	Custom sizes, other door thickness, other options; Contact Customer Service.	

	1-13/16"
1" ↓	
ize	
ORDER SIZE = OPENING SIZE	
SIZE = O	
- ORDER	
-	
<u> </u>	
	1/4"

Order Format: 7001	L				
Example: 700TL G1212B	Option S,J,E	W	Н	Color	

AIR	
LOU	VERS

Distributor:	Width:x Height:
Architect:	Quantity:
Contractor:	Model:
Project:	Date: Version: ALPDS1404

800-554-6077 QUOTES@ACTIVARCPG.COM ORDERS@ACTIVARCPG.COM SALES@ACTIVARCPG.COM FAX: 952-835-2218

VISIT <u>WWW.ACTIVARCPG.COM</u> FOR THE MOST UPDATED PRODUCT INFORMATION • AN ACTIVAR CONSTRUCTION PRODUCTS COMPANY MFG: COMMERCE CA, BLOOMINGTON, MN • WAREHOUSES: LANCASTER PA, ATLANTA GA, CHICAGO IL, SEATTLE WA, FORT MYERS FL, DALLAS TX