

**Overview**

- This single output power supply/charger converts a 115VAC/60Hz input into one (1) 12VDC non-power limited output.

Specifications

- | | |
|--|---|
| <ul style="list-style-type: none">• 12VDC output.• 10 amp of continuous supply current.• Input 115VAC / 60Hz, 1.9 amp.• Input fuse rated @ 3.5 amp/250V.• Filtered and electronically regulated output.• Short circuit and thermal overload protection.• Built-in charger for sealed lead acid or gel type batteries.• Maximum charge current .7 amp.• Automatic switch over to stand-by battery when AC fails (zero voltage drop).• AC fail supervision (form "C" contacts). | <ul style="list-style-type: none">• Low battery supervision (form "C" contacts).• Battery presence supervision (form "C" contacts).• AC input and DC output LED indicators.• Enclosure:<ul style="list-style-type: none">- Combination knockouts are 1/2" and 3/4".- Accommodates one (1) 12VDC/12AH battery.• Product weight:<ul style="list-style-type: none">- AL1012ULX: 9.3 lbs.• Shipping weight:<ul style="list-style-type: none">- AL1012ULX: 10.6 lbs. |
|--|---|

Agency Approvals

UL 294 UL Listed for Access Control
System Units.

Enclosure Dimensions
15.5"H x 12"W x 4.5"D

