

Overview

- These multi-agency approved multi-output power supply/chargers convert a 115VAC/60Hz input to four (4) 24VDC outputs.

AL1024ULXPD4

- Fuse protected non-power limited outputs rated @ 3.5 amp each.
- Grey enclosure.

AL1024ULXPD4R

- Red enclosure.

AL1024ULXPD4CB

- Class 2 Rated PTC protected power limited outputs rated @ 2.5 amp each.
- Grey enclosure.

AL1024ULXPD4CBR

- Red enclosure.

Specifications

- | | |
|---|--|
| <ul style="list-style-type: none">• 24VDC outputs.• 10 amp of continuous supply current for Access Control applications.• 8 amp of continuous supply current for Fire Alarm applications.• Four (4) protected outputs.• Input 115VAC / 60Hz, 4.4 amp.• Input fuse rated @ 3.5 amp/250V.• Filtered and electronically regulated outputs.• Short circuit and thermal overload protection.• Built-in charger for sealed lead acid or gel type batteries. | <ul style="list-style-type: none">• Maximum charge current 3.6 amp.• Automatic switch over to stand-by battery when AC fails (zero voltage drop).• AC fail supervision (form "C" contacts).• Low battery supervision (form "C" contacts).• Battery presence supervision (form "C" contacts).• AC input and DC output LED indicators.• Enclosure:<ul style="list-style-type: none">- Combination knockouts are 1/2" and 3/4"- Accommodates up to two (2) 12VDC/12AH batteries. |
|---|--|

Agency Approvals

- | | |
|---------|--|
| UL 294 | UL Listed for Access Control System Units. |
| UL 1481 | UL Listed Standard for Safety for Fire Protective Signaling Systems. |



- | |
|---|
| CUL Listed - CSA Standard C22.2 No.205-M1983, Signal Equipment. |
|---|

Enclosure Dimensions

15.5"H x 12"W x 4.5"D

