

**Overview**

- This power supply converts a 115VAC or 230VAC 50/60Hz input, to a 2.5 amp of continuous supply current @ 12VDC or 24VDC power limited output.

AL300ULXD

- 115VAC 50/60Hz, .9 amp or 230VAC 60Hz .45 amp input.
- Class 2 Rated power limited output.

Specifications

- | | |
|--|---|
| <ul style="list-style-type: none">• 12VDC or 24VDC selectable output.• 2.5 amp of continuous supply current output.• Input fuse rated @ 3.5 amp/250V.• Filtered and electronically regulated outputs.• Short circuit and thermal overload protection.• Built-in charger for sealed lead acid or gel type battery backup.• Maximum charge current .6 amp.• Zero voltage drop upon transfer to battery backup.• AC fail supervision (form "C" contact) | <ul style="list-style-type: none">• Low battery supervision (form "C" contact).• AC input and DC output LED indicators.• Enclosure:<ul style="list-style-type: none">- Combination knockouts are 1/2" and 3/4"- Accommodates up to two (2) 12VDC/12AH batteries.• Product weight:<ul style="list-style-type: none">- AL300ULXD: 11.7 lbs.• Shipping weight:<ul style="list-style-type: none">- AL300ULX: 13.0 lbs. |
|--|---|

Agency Approvals

- | | |
|---------|---|
| UL 294 | UL Listed for Access Control System Units. |
| UL 603 | UL Listed Standard for Power Supplies for Use with Burglar-Alarm Systems. |
| UL 1069 | UL Listed Hospital Signaling and Nurse Call Equipment. |
| UL 1481 | UL Listed Standard for Safety for Fire Protective Signaling Systems. |



CE Approved.

Enclosure Dimensions

15.5"H x 12"W x 4.5"D

