

**Overview**

- The AL600ULXD power supply converts a 115VAC or 230VAC / 50/60Hz input, to a 12VDC or 24VDC non-power limited output.

**Specifications**

- |                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>• Switch selectable 12VDC or 24VDC non-power limited output.</li><li>• 12VDC or 24VDC @ 6 amp supply current.</li><li>• Input 115VAC / 60Hz, 1.9 amp or 230VAC 50/60Hz, .95 amp.</li><li>• Maximum charge current .7 amp.</li><li>• Filtered and electronically regulated output.</li><li>• Built-in charger for sealed lead acid or gel type batteries.</li><li>• Automatic switch over to stand-by battery when AC fails.</li></ul> | <ul style="list-style-type: none"><li>• AC input and DC output LED indicators.</li><li>• AC fail supervision (form "C" contacts).</li><li>• Low battery and battery presence supervision (form "C" contacts).</li><li>• Short circuit and thermal overload protection.</li><li>• Unit is complete with power supply, enclosure, cam lock and open frame transformers.</li><li>• Includes battery leads.</li></ul> |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Agency Approvals**

UL 294    UL Listed for Access Control System Units.  
UL 1481   UL Listed Standard for Safety for Fire Protective Signaling Systems.



European Conformity.

## **Enclosure Dimensions**

15.5"H x 12"W x 4.5"D

