



Overview

- These linear power supply/charger is specifically designed to provide the power needed by the most demanding security and access control applications. It will convert a 115VAC 50/60Hz input to a 2.5 amp, 12VDC or 24VDC output.

LPS3C12X

- 12VDC output.
- Input 115VAC 50/60Hz rated @ .5 amp.

LPS3C24X

- 24VDC output.
- Input 115VAC 50/60Hz rated @ .7 amp.

Specifications

- 2.5 amp supply current.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.
- Built-in charger for sealed lead acid or gel type batteries.
- Maximum charge current .5 amp.
- Automatic switch over to stand-by battery when AC fails (zero voltage drop).
- AC input and DC output LED indicators.
- Fused battery protection (circuit breaker available).

- Includes battery leads.
- Enclosure:
 - Combination knockouts are 1/2" and 3/4"
 - Accommodates up to one (1) 12VDC/12AH batteries.
- Product weight:
 - LPS3C12X: 11.1 lbs.
 - LPS3C24X: 12.1 lbs.
- Shipping weight:
 - LPS3C12X: 12.3 lbs.
 - LPS3C24X: 13.4 lbs.

Enclosure Dimensions

15.5"H x 12"W x 4.5"D

