

RIPPING SAW BLADE

"Euro-Rip" With Anti-Kickback Feature



Amana Tool

- Designed for ripping hardwood and softwood, this exceptional blade cuts fast and smooth
- The flat-top grind and the high positive hook angle reduce feed effort
- The anti-kickback design limits the thickness of chip taken to offer a safer cut
- Cooling slots in the body prevent excessive heat build up

Packing & Sold In: Each

| Item# | Outside Diameter | # of Teeth | Teeth Configuration | Hook Angle | Kerf Width | Plate Thickness | Coating | Cooling Expansion Slots | Copper Plugs | Bore |
|----------|---------------------|---------------|------------------------|---------------|---------------|--------------------|---------|----------------------------|-----------------|------|
| AARB1020 | 10" | 20 | Flat Top | 20° | .126" | .087" | None | Yes | Yes | 5/8" |



RIPPING SAW BLADE

Glue Line Ripping


- This exceptional blade cuts so cleanly that there's no need for sanding or jointing after the cut before glue joining boards
- The precision triple chip grind & extra high hook angle allows aggressive feed rates, yet produces an extra smooth cut finish
- The thick plate minimizes vibration. Can be used on table saws, sliding table saws, single and gang rip operations

Packing & Sold In: Each

| Item# | Outside Diameter | # of Teeth | Teeth Configuration | Hook Angle | | | Coating | Cooling Expansion Slots | Copper Plugs | Bore |
|----------|---------------------|---------------|------------------------|---------------|-------|-------|---------|----------------------------|-----------------|------|
| AA610301 | 10" | 30 | Triple Chip | 22° | .145" | .095" | None | Yes | Yes | 5/8" |
| AA612401 | 12" | 40 | Triple Chip | 22° | .160" | .110" | None | Yes | Yes | 1" |



RIPPING & CROSSCUT COMBINATION SAW BLADE



- For ripping and crosscutting of natural woods
- Teeth consist of four ATB followed by one square raker
- · Large gullets in the saw blade body allow for deeper cuts and improved chip ejection

Packing & Sold In: Each

| Item# | Outside Diameter | # of Teeth | Grind | Kerf Width | Plate Thickness | Hook Angle | Bore |
|------------|---------------------|---------------|-------|---------------|--------------------|---------------|------|
| AAMD10-500 | 10" | 50 | 4 &1 | .126" | .087" | 10° | 5/8" |



RIPPING & CROSSCUT SAW BLADE

4 ATB & 1 Flat

For cutting/grooving of soft and hard woods with or against the grain.

Packing & Sold In: Each

| Item# | Outside Diameter | # of Teeth | Grind | Hook Angle | Bore |
|-------------|-------------------------|------------|---------------|-------------------|------|
| WW611625450 | 10" | 50 | 4 ATB, 1 Flat | 15° | 5/8" |





😾 WÜRTH

