



High Flow Extinguishers

7595 GADSDEN HWY. ♦ TRUSSVILLE, ALABAMA 35173 ♦ PH: (205) 655-3271 ♦ FAX: 1-800-654-5980 ♦ email:sales@amerex-fire.com

Amerex is now manufacturing High Flow portable fire extinguishers for use where non-rated extinguishers are needed. The extinguishers utilize the same hardware as Amerex standard products. The High Flow extinguishers have a 6 year warranty and are manufactured to the same U.L. specifications as our rated products.

FEATURES:

Same hardware and valve components as our standard models

Twice the flow rate of standard models

Chrome plated brass valve

Stainless steel handle and lever

Large loop stainless steel pull pin with lanyard

Meets DOT requirements

UL listed

USCG Approved



SPECIFICATIONS						
Model Number	720	760	721	761	722	762
Agent	ABC	ABC	REGULAR	REGULAR	PURPLE K	PURPLE K
Capacity (lbs.)	10	20	10	20	10	20
Application	HOSE & NOZZLE		HOSE & NOZZLE		HOSE & NOZZLE	
U/L Rating	1A:20B:C	4A:60B:C	20B:C	60B:C	20B:C	60B:C
Shipping Weight (lbs.)	19	39	19	39	19	39
Discharge Time (sec.)	9½	19	9½	19	9½	19
Discharge Rate (lbs./sec.)	1.35	1.20	1.21	1.11	1.24	1.08
Discharge Range (ft.)	15-25	15-25	15-25	15-25	15-25	15-25
Height (in.)	20½	24	20½	24	20½	24
Width (in.)	8¾	10¼	8¾	10¼	8¾	10¼
Depth (in.)	5	7	5	7	5	7
Temperature Range (°F)	-65°F to 120°F					
Bracket Type	WALL		WALL		WALL	

MADE IN U.S.A.!