



Amerex Corporation

Quality is Behind the Diamond®



Wheeled Extinguishers

STORED PRESSURE

50, 125/150 lb. Stored Pressure - ABC, REGULAR, PURPLE K Dry Chemical

These commercial stored pressure extinguishers are available in a choice of two sizes and three chemical options. The carriage design on both sizes provides cage type protection for the agent cylinder as well as a well balanced platform for transportation and operation. The narrow width and easy rolling semi-pneumatic rubber tire wheels allow one person movement through narrow aisles, doorways and in confined areas. Chemical and pressure is sealed in the agent cylinder, ready for instant actuation and is always protected from contamination. Stored pressure wheeled extinguishers are less expensive to purchase as well as easier and less costly to maintain and service.

FEATURES:

- Brass Hose Fittings
- Quick Opening Valves
- Live Swivel on Discharge Valve
- Brass Valve - Chrome Plated on 125 lb. & 150 lb. Models
- Lifting Eyes on 125 lb. & 150 lb. Models
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- DOT/TC Cylinders
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- Chrome Forged Brass Fill Cap on 125 lb. & 150 lb. Models
- Large fill opening on 125 lb. & 150 lb. Models
- Stainless Steel Fasteners
- Stainless Steel Gauge Guard on 125 lb. & 150 lb. Models
- 6 Year Warranty



Test Standards:

CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

Available Options:

- Tow Loop

SPECIFICATIONS	50 LB. DRY CHEMICAL			125/150 LB. DRY CHEMICAL		
MODEL NUMBER	495	496	497	488	489	490
AGENT TYPE	ABC	REGULAR	PURPLE K	ABC	REGULAR	PURPLE K
UL & ULC RATING	20A:160B:C	160B:C	160B:C	30A:240B:C	240B:C	320B:C
CAPACITY (LBS. / KG)	50 / 22.68			125 / 56.7	150 / 68.0	125 / 56.7
SHIPPING WT. (LBS. / KG)	174 / 78.88			344 / 155.95	369 / 167.28	344 / 155.95
HEIGHT (IN. / CM)	46 / 116.84			53.5 / 136.0		
WIDTH (IN. / CM)	21.5 / 54.61			28 / 71.12		
DEPTH (IN. / CM)	24 / 60.96			40 / 101.6		
DISCHARGE TIME (SEC.)	35			48		
DISCHARGE RANGE (FT. / M)	25-35 / 7.62 - 10.66			30-40 / 9.1-12.2		
OPERATING TEMP. (F / C)	-40° to +120° / -40° to +49°			-65° to 120° / -54° to +49°		
HOSE LENGTH (FT. / M)	25 / 7.62			50 / 15.2		
HOSE DIAMETER (IN. / CM)	.50 / 1.27			.75 / 1.90		
WHEELS [SEMI-PNEU] (IN. / CM)	12.5 X 3.5 / 31.75 X 8.89			16 X 4 / 40.64 X 10.16		
USCG APPROVED	YES					

DESIGNED AND ASSEMBLED IN USA

STORED PRESSURE

HIGH PERFORMANCE 125/250 lb. - ABC, REGULAR, PURPLE K Dry Chemical

HIGH PERFORMANCE Stored Pressure units are the finest performing dry chemical wheeled fire extinguishers available anywhere! They have a tremendous flow rate, vertical and horizontal range, fire killing ability and operator protection. Wheels are wide footprint 36" X 6".



250 LB.

FEATURES:

- Brass Hose Fittings
- Quick Opening Valves
- Live Swivel on Discharge Valve
- Brass Valve - Chrome Plated
- Heavy Duty Hot Dip Galvanized Steel Cylinders, Carriage, Hose Rack, and Wheels
- Lifting Eyes
- DOT Cylinders (DOT/TC Model 690)
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- Chrome Plated Forged Brass Fill Cap
- Large fill opening
- Stainless Steel Fasteners
- Stainless Steel Gauge Guard
- 12 Year Warranty



125 LB.

Available Options:

- Optional 36" x 6" wheels with non-sparking rubber treads

Test Standards:

CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

Available Options:

- Optional 36" x 6" wheels with non-sparking rubber treads

SPECIFICATIONS		DRY CHEMICAL		
MODEL NUMBER	573	574	575	690
AGENT TYPE	ABC	REGULAR	PURPLE K	PURPLE K
UL & ULC RATING	40A:160B:C	160B:C	160B:C	120B:C
CAPACITY (LBS. / KG)	250 / 113.4			125 / 56.7
SHIPPING WT. (LBS. / KG)	775 / 351.3			400 / 181.4
HEIGHT (IN. / CM)	60 / 152.4			53.5 / 135.9
WIDTH (IN. / CM)	37 / 93.98			34 / 86.4
DEPTH (IN. / CM)	44 / 111.76			38.5 / 97.8
DISCHARGE TIME (SEC.)	50	40	42	30
DISCHARGE RANGE (FT. / M)	60 - 80 / 18.19 - 24.26			50 - 55 / 15.24 - 16.76
OPERATING TEMP. (F / C)	-40° to +120° / -40° to +49°			
HOSE LENGTH (FT. / M)	50 / 15.24			
HOSE DIAMETER (IN. / CM)	1 / 2.54			
WHEELS [STEEL] (IN. / CM)	36 X 6 / 91.44 X 15.24			
USCG APPROVED	YES			

DESIGNED AND ASSEMBLED IN USA

NITROGEN CYLINDER OPERATED

125/150, 300/350 lb. Direct Pressure - ABC, REGULAR, PURPLE K Dry Chemical

125 lb. ABC & Purple K and 150 lb. Regular Direct Pressure extinguishers utilize a 23 ft³ nitrogen cylinder with a "quick opening brass valve" to pressurize and completely discharge the agent cylinder. The compact size and 16" semi-pneumatic tires allow easy maneuvering and operation by one person, through narrow doorways and aisles. A 4" stainless steel fill opening with rugged chrome plated brass cap makes servicing easier. For large hazards choose the 300 lb. ABC or Purple K or 350 lb. Regular Direct Pressure extinguishers with a "quick opening" 55 ft³ nitrogen cylinder. They provide quality and economical fire protection, large volume capacity for extra high hazard areas with single person transport and operation. The 36" X 6" wide steel wheels make movement possible in sandy or soft soil.



FEATURES:

- Stainless Steel Collars
- Chrome Plated Brass Fill Caps
- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- Lifting Eyes
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- DOT/TC Nitrogen Cylinder with Quick Opening Brass Valve
- 6 Year Warranty



Available Options:

- 100 ft. Hose
- Fill Cap with Pressure Indicator

Test Standards:

CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

Available Options:

- 36" x 6" wheels with non-sparking rubber treads
- 100 ft. hose
- Fill Cap with Pressure Indicator

SPECIFICATIONS	125/150 LB. DRY CHEMICAL			300/350 LB. DRY CHEMICAL		
MODEL NUMBER	450	451	452	491	492	493
AGENT TYPE	ABC	REGULAR	PURPLE K	ABC	REGULAR	PURPLE K
UL & ULC RATING	30A:240B:C	240B:C	320B:C	40A:320B:C	320B:C	320B:C
CAPACITY (LBS.)	125 / 57	150 / 68	125 / 57	300 / 136.07	350 / 158.75	300 / 136.07
SHIPPING WT. (LBS.)	335 / 152	360 / 163	335 / 152	743 / 337.01	793 / 359.69	743 / 337.01
HEIGHT (IN. / CM)	45 / 115			57 / 144.78		
WIDTH (IN. / CM)	24 / 61			34 / 86.36		
DEPTH (IN. / CM)	36 / 92			39 / 99.06		
DISCHARGE TIME (SEC.)	52	60	53	60	70	67
DISCHARGE RANGE (FT. / M)	30 - 40 / 9 - 12					
OPERATING TEMP. (F / C)	-65° to +120° / -54° to +49°					
NITROGEN CYLINDER (CU. FT. / LITER)	23 / 651			55 / 1557.43		
SAFETY BURST DISC RANGE (PSI / kPa)	400 - 500 / 2760 - 3450					
HOSE LENGTH (FT. / M)	50 / 15.24					
HOSE DIAMETER (IN. / CM)	.75 / 1.90			1 / 2.54		
WHEELS [SEMI-PNEUMATIC / STEEL] (IN. / CM)	16 X 4 / 40.64 X 10.16			36 X 6 / 91.44 X 15.24		
USCG APPROVED	YES					

DESIGNED AND ASSEMBLED IN USA

NITROGEN CYLINDER OPERATED

125/150 lb. Regulated Pressure - ABC, REGULAR, PURPLE K Dry Chemical

These 110 ft³ nitrogen cylinder operated models feature a pressure regulator and two wheel options. The older, traditional design allows for adequate pressure to assure a smooth, complete discharge of the dry chemical with pressure reserve for blowing down the discharge hose. Choose either the 16" semi-pneumatic rubber tire or 36" X 2½" steel wheels according to the area to be protected. Easy to transport and operate by one person.



Available Options:

- Fill Cap with Pressure Indicator

FEATURES:

- Stainless Steel Collars
- Chrome Plated Brass Fill Caps
- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- Lifting Eyes
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- DOT/TC Nitrogen Cylinder with Quick Opening Brass Valve
- Chrome Plated Brass Regulator
- 6 Year Warranty



Available Options:

- 36" x 6" or 36" x 2½" wheels with non-sparking treads
- Fill Cap with Pressure Indicator

Test Standards:

CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

SPECIFICATIONS	125/150 LB. DRY CHEMICAL SEMI-PNEAUMATIC WHEELS			125/150 LB. DRY CHEMICAL STEEL WHEELS		
MODEL NUMBER	467	468	469	470	471	472
AGENT TYPE	ABC	REGULAR	PURPLE K	ABC	REGULAR	PURPLE K
UL & ULC RATING	30A:240B:C	240B:C	320B:C	30A:240B:C	240B:C	320B:C
CAPACITY (LBS. / KG)	125 / 57	150 / 68	125 / 57	125 / 57	150 / 68	125 / 57
SHIPPING WT. (LBS. / KG)	404 / 183	429 / 195	404 / 183	432 / 196	457 / 207	432 / 196
HEIGHT (IN. / CM)	52 / 132					
WIDTH (IN. / CM)	26 / 66			28 / 71		
DEPTH (IN. / CM)	38 / 97			45 / 114		
DISCHARGE TIME (SEC.)	48	53	52	48	53	52
DISCHARGE RANGE (FT. / M)	30 - 40 / 9 - 12					
OPERATING TEMP. (F / C)	-65° to +120° / -54° to +49°					
NITROGEN CYLINDER (CU. FT. / LITER)	110 / 3115					
HOSE LENGTH (FT. / M)	50 / 15.24					
HOSE DIAMETER (IN. / CM)	.75 / 1.90					
WHEELS [SEMI-PNEUMATIC / STEEL] (IN. / CM)	16 X 4 / 40.64 X 10.16			36 X 2.5 / 91.44 X 6.35		
USCG APPROVED	YES					

DESIGNED AND ASSEMBLED IN USA



CLEAN AGENT EXTINGUISHERS

65 lb. & 150 lb. - Stored Pressure Halotron I™

The Amerex Halotron I™ extinguishers feature the same qualities found in all Amerex products and adds the convenience of a "clean" extinguishing agent. Halotron I™ extinguishing agent has proven itself as the leader in the hunt for an alternative "clean" agent by being the only alternative "clean" agent to obtain FAA approvals for both ramp use (ARFF Vehicle) and on-board an aircraft. Combining the quality of Amerex products with a proven alternative "clean" agent, the Amerex Halotron I™ wheeled extinguishers offer you the best value in the industry.

- ⇒ **EPA approved "Clean Agent" for Class A, B, and C hazards**
- ⇒ **Low GWP (Global Warming Potential)**
- ⇒ **Low ODP (Ozone Depletion Potential)**
- ⇒ **Short Atmospheric Lifetime**
- ⇒ **Maximum visibility during discharge**
- ⇒ **No thermal or static shock**
- ⇒ **No electrical conductivity back to the operator**

FEATURES:

- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Reflective stripes
- Tow loops
- Stainless Steel Fasteners
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- DOT/TC Cylinders
- Stainless Steel Gauge Guard
- Quick Opening Valves
- Chrome Plated Brass Valve
- Quick Release Discharge Hose
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- 6 Year Warranty

Available Options:

- 36" x 6" wheels with non-sparking rubber treads

Test Standards:

CAN/ULC S556 & ANSI/UL 2129
CAN/ULC S508 & ANSI/UL 711

SPECIFICATIONS		HALOTRON I™	
MODEL NUMBER	B673	B674	B675
AGENT TYPE	CLEAN AGENT		
UL & ULC RATING	4A:80B:C	10A:120B:C	
CAPACITY (LBS. / KG)	65 / 29.5	150 / 68	
SHIPPING WT. (LBS. / KG)	286 / 129.7	512 / 232.2	610 / 276.7
HEIGHT (IN. / CM)	58 / 147.3	64 / 162.6	
WIDTH (IN. / CM)	28 / 71.1	30 / 76.2	37 / 94
DEPTH (IN. / CM)	39 / 99.1	42 / 106.7	43 / 109.2
DISCHARGE TIME (SEC.)	22	38	
DISCHARGE RANGE (FT. / M)	30 - 45 / 9.1 - 13.7		
OPERATING TEMP. (F / C)	-40° to 120° / -40° to +49°		
HOSE LENGTH (FT. / M)	50 / 15.2		
HOSE DIAMETER (IN. / CM)	.75 / 1.9		
WHEELS [SEMI-PNEUMATIC / STEEL] (IN. / CM)	16 X 4 / 40.64 X 10.2		36 X 2.5 / 91.44 X 6.35
USCG APPROVED	YES		

DESIGNED AND ASSEMBLED IN USA

CLEAN AGENT EXTINGUISHERS

3M™ NOVEC 1230™ Fire Protection Fluid has a Global Warming Potential of 1 and an atmospheric life of just 5 days making it the long term sustainable choice that also has the greatest margin of safety of any of the chemical agents in the marketplace today.

FEATURES:



- Environmentally friendly 3M™ Novec™ 1230 Clean Agent (0 ODP - 1 GWP)
- Brass, chrome plated operating valve
- 125 PSI Operating Pressure
- Heavy duty steel cylinder, carriage and hose hanger assembly
- DOT Cylinders
- Quick release 40 ft. discharge hose with brass/chrome plated ball type shut-off nozzle
- Pressure gauge protected by a stainless steel gauge guard
- Corrosion resistant lime/yellow polyester paint finish
- UL/ULC Bilingual (English/ Spanish) Nameplates with Bar Code
- Large instruction pictogram
- Operating temperature range: -40° to +120° F.
- 6 year manufacturer's warranty

SPECIFICATIONS	3M™ Novec 1230™	
Model Number	775	776R
Agent	Novec 1230	
Capacity (lbs.)	150	150
UL & ULC Rating	3A:80B:C	3A:80B:C
Shipping Weight (lbs.)	395	460
Discharge Time (sec.)	22	
Cylinder - DOT 4BW240		
Operating Press (psi)	125	
Test Pressure (psi)	480	
Burst Pressure (minimum - psi)	960	
Discharge Range (ft.)	30	
Hose Length (ft.)	40	
Hose Diameter (in.)	1.0	
Wheels (Semi-pneumatic Model 775) (in.)	16 x 4	36 x 2.5
Height (in.)	61	61
Width (in.)	29	35
Depth (in.)	42	42
USCG Approved	YES	

HALON 1211 is a liquified gas, pressurized with nitrogen, which discharges as a vapor causing no cold or static shock and no impairment of the operator's vision. This "CLEAN" agent quickly penetrates difficult to see and hard to reach areas and leaves no residue. It is recommended for protection of delicate, sensitive and expensive computers, electrical equipment, tapes and film, automotive and aircraft engines, laboratory chemicals and equipment.

Quality industrial grade hardware, "CLEAN" agent, light weight, good discharge range and excellent fire extinguishing ability.

SPECIFICATIONS	HALON 1211
MODEL NUMBER	600
AGENT TYPE	Halon 1211
CAPACITY (LBS.)	150
SHIPPING WEIGHT (LBS.) EMPTY / FULL	205 / 355
DISCHARGE TIME (SEC.)	43
CYLINDER - DOT 4BW240	
OPERATING PRESSURE (PSI)	200
TEST PRESSURE (PSI)	500
BURST PRESSURE (MINIMUM - PSI)	960
DISCHARGE RANGE (FT.)	35-40
HOSE LENGTH (FT.)	50
HOSE DIAMETER (IN.)	.75
WHEELS (SEMI-PNEUMATIC) (IN.)	16 x 4
HEIGHT (IN.)	59
WIDTH (IN.)	29
DEPTH (IN.)	42

FEATURES:

- Brass Hose Fittings
- Quick Opening Valves
- Live Swivel on Discharge Valve
- Chrome Plated Brass Valve
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- DOT/TC Cylinders
- UL/ULC Bilingual (English/ Spanish) Nameplates with Bar Code
- Corrosion resistant lime/yellow polyester paint finish
- Large instruction pictogram
- Stainless Steel Fasteners
- Stainless Steel Gauge Guard
- 1 Year Warranty



DESIGNED AND ASSEMBLED IN USA

SPECIALTY EXTINGUISHERS

33 Gal. Direct Pressure Premix Foam

The Model 630 contains a premixed alcohol resistant AFFF ATC foam which is highly effective on Class B fuel fires and a penetrating and wetting agent on fires involving Class A materials. Excellent when used as a vapor suppressant on fuel spills to prevent ignition. Quality hardware throughout including the unique agent cylinder fabricated entirely of stainless steel - no interior coatings are necessary. Model 630 meets NFPA 418 requirements for H-1 category helicopter pad protection.



FEATURES:

- Stainless Steel Collars
- Chrome Plated Brass Fill Caps
- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- DOT/TC Nitrogen Cylinder with Quick Opening Brass Valve
- 5 Year Warranty

Test Standards:

CAN/ULC S554 & ANSI/UL 8
CAN/ULC S508 & ANSI/UL 711

SPECIFICATIONS	33 GAL. FOAM
MODEL NUMBER	630
AGENT TYPE	AFFF ATC
UL & ULC RATING	20A:160B
CAPACITY (GAL. / LITER)	33 / 124.91
SHIPPING WT. (LBS. / KG)	390 / 176.88
HEIGHT (IN. / CM)	57 / 144.78
WIDTH (IN. / CM)	34 / 86.36
DEPTH (IN. / CM)	39 / 99.06
DISCHARGE TIME (SEC.)	60
DISCHARGE RANGE (FT. / M)	30 - 40 / 9.1 - 12
OPERATING TEMP. (F / C)	+35° to 120° / +2° to +49°
NITROGEN CYLINDER (CU. FT. / LITER)	23 / 651.29
SAFETY BURST DISC RANGE (PSI / kPa)	400 - 500 / 2760 - 3450
HOSE LENGTH (FT. / M)	50 / 15.2
HOSE DIAMETER (IN. / CM)	1 / 2.54
WHEELS [STEEL] (IN. / CM)	36 X 6 / 91.44 X 15.24
USCG APPROVED	YES

Available Options:

- Optional 36" x 6" wheels with non-sparking rubber treads
- Fill Cap with Pressure Indicator

50 & 100 lb. CARBON DIOXIDE

Large volume CO₂ protection provided in either 50 or 100 lb. (2 - 50 lb. cylinders) wheeled extinguishers. Rugged construction and easy to operate with a "quick opening" 'T' handle valve and horn mounted shut-off valve. A logical choice in areas where a Class B:C non-contaminating agent is required and where hand portable extinguishers do not provide adequate protection.

FEATURES:

- Heavy Duty Steel Carriages
- Quick Opening Brass Valve
- Squeeze Grip Chrome Plated Discharge Valve
- Reinforced Wire Braided Hose and Shock Resistant Horn to Reduce Static Electricity
- Brass Hose Fittings
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- DOT/TC Cylinder with Quick Opening Brass Valve
- Clean, Non-Contaminating Odorless Gas
- 5 Year Warranty



SPECIFICATIONS	CARBON DIOXIDE	
MODEL NUMBER	333	334
AGENT TYPE	CARBON DIOXIDE	
UL & ULC RATING	20B:C	
CAPACITY (LB. / KG)	50 / 22.7	100 / 45.4
SHIPPING WT. (LB. / KG)	257 / 116.6	461 / 209.3
HEIGHT (IN. / CM)	47 / 119.5	
WIDTH (IN. / CM)	23 / 58.4	
DEPTH (IN. / CM)	48 / 122	
DISCHARGE TIME (SEC.)	44+-5	74 +-8
DISCHARGE RANGE (FT. / M)	10 - 15 / 3.04 - 4.57	
OPERATING TEMP. (F / C)	-22° to +120° / -30° to +49°	
HOSE LENGTH (FT. / M)	40 / 12.1	
HOSE DIAMETER (IN. / CM)	.25 / .635	
WHEELS [FULL PNEUMATIC] (IN. / CM)	16 X 4 / 40.64 X 10.16	
USCG APPROVED	YES	

Available Options:

- 100 lb. Stationary Design - Model 335
- Semi-Pneumatic Wheels

Test Standards:

CAN/ULC S503 & ANSI/UL 154
CAN/ULC S508 & ANSI/UL 711

DESIGNED AND ASSEMBLED IN USA

CLASS D Dry Powder:

150 lb. Regulated Pressure SODIUM CHLORIDE

250 Lb. Regulated Pressure COPPER POWDER

Two choices for large volume Class D (flammable metal) protection. Model 680 (Sodium Chloride) is effective on magnesium, sodium, potassium and sodium potassium alloy fires. Model 681 (Copper Powder) designed specifically for fighting difficult lithium fires. Well balanced for quick transport on 36" non-sparking rubber tread steel wheels. Both are pressurized with Argon and regulated to a low 125 psi to avoid disrupting the burning materials.



Extension Wand is Standard
(Nozzle Optional)

FEATURES:

- Stainless Steel Collars
- Chrome Plated Brass Fill Caps
- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- DOT/TC Argon Cylinder with Quick Opening Brass Valve
- Brass Regulator
- 6 Year Warranty

Test Standards:

CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

SPECIFICATIONS	CLASS D	
MODEL NUMBER	680	681
AGENT TYPE	SUPER D (SODIUM CHLORIDE)	COPPER
CAPACITY (LB.)	150 / 68	250 / 113.33
SHIPPING WT. (LBS. / KG)	444 / 201.28	544 / 246.61
HEIGHT (IN. / CM)	52 / 132.08	
WIDTH (IN. / CM)	28 / 71.12	
DEPTH (IN. / CM)	45 / 114.3	
DISCHARGE TIME (SEC.)	80	120
DISCHARGE RANGE (FT./M)		
WITH NOZZLE	20 - 30 / 6.57 - 9.86	
WITH APPLICATOR	4 - 8 / 1.31 - 2.62	
OPERATING TEMP. (F / C)	-40° to 120° / -40° to +49°	
ARGON CYLINDER (CU. FT. / LITER)	110 / 3115	
HOSE LENGTH (FT. / M)	25 / 7.70	
HOSE DIAMETER (IN. / CM)	.75 / 1.90	
WHEELS [STEEL] (IN. / CM)	36 X 2.5 / 91.44 X 6.35	
USCG APPROVED	NO	
FM APPROVED	YES	

Available Options:

- 36" x 6" wheels with non-sparking treads
- Fill Cap with Pressure Indicator

DESIGNED AND ASSEMBLED IN USA

WET CHEMICAL WHEELED EXTINGUISHERS

Model 325R utilizes a Class "K" liquid agent that contains a special potassium acetate base formula. More efficient cooking appliances and use of vegetable based cooking oils require the use of extinguishers with greater fire fighting capacity and cooling effect to combat these very hot and difficult fires. This water based agent extinguisher also provides excellent capabilities for Class "A" hazards. The superior fire fighting capability of the Wet Chemical agent is placed exactly where you aim to minimize clean up.

A single wheeled extinguisher will protect a fryer containing up to 560 gallons of vegetable shortening and is intended only for appliance protection of large commercial deep fat fryers. The energy source to the appliance should be shut off as soon as conditions are safe to do so. Following the "INSTRUCTIONS" as shown on the nameplate, completely discharge the extinguisher onto the burning oil to allow cooling and prevent re-ignition. This extinguisher is not intended to take the place of a fixed fire suppression system for large commercial/industrial cooking operations. This extinguisher should only be used as supplemental fire protection in addition to a properly installed and designed automatic fire suppression system.

SPECIFICATIONS	32.5 GAL. CLASS "K"
MODEL NUMBER	325R
AGENT TYPE	WET CHEMICAL
CAPACITY (GAL. / LITER)	32.5 / 123.02
SHIPPING WT. (LBS. / KG)	460 / 208.65
HEIGHT (IN. / CM)	57 / 144.78
WIDTH (IN. / CM)	34 / 86.36
DEPTH (IN. / CM)	39 / 99.06
DISCHARGE TIME (SEC.)	210
DISCHARGE RANGE (FT. / M)	15-20 / 4.57 - 6.1
OPERATING TEMP. (F / C)	+32° to 120° / 0° to 49°
NITROGEN CYLINDER (CU. FT. / LITER)	23 / 651.29
SAFETY BURST DISC RANGE (PSI / kPa)	400 - 500 / 2760 - 3450
HOSE LENGTH (FT. / M)	50 / 15.2
HOSE DIAMETER (IN. / CM)	3/4 / 1.91
WHEELS [STEEL] (IN. / CM)	36 X 6 / 91.44 X 15.24
UL / FM LISTING	N/A

FEATURES:

- Stainless Steel Agent Cylinder
- Chrome Plated Brass Fill Caps
- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Large instruction pictogram
- DOT/TC Nitrogen Cylinder with Quick Opening Brass Valve
- 36" x 6" Wheels with Rubber Treads
- Stainless Steel Spray Nozzle
- 5 Year Warranty



GALVANIZED EXTINGUISHERS

SPECIFICATIONS	125 LB. DRY CHEMICAL	300 LB. DRY CHEMICAL
MODEL NUMBER	4520S	4930S
AGENT TYPE	PURPLE K	PURPLE K
UL & ULC RATING	320B:C	320B:C
CAPACITY (LBS. / KG)	125 / 57	300 / 136.07
SHIPPING WT. (LBS. / KG)	335 / 152	743 / 337.01
HEIGHT (IN. / CM)	45 / 115	57 / 144.78
WIDTH (IN. / CM)	24 / 61	34 / 86.36
DEPTH (IN. / CM)	36 / 92	39 / 99.06
DISCHARGE TIME (SEC.)	53	67
DISCHARGE RANGE (FT. / M)	30 - 40 / 9 - 12	
OPERATING TEMP. (F / C)	-65° to +120° / -54° to +49°	
NITROGEN CYLINDER (CU. FT. / LITER)	23 / 651	55 / 1557.43
SAFETY BURST DISC RANGE (PSI / kPa)	400 - 500 / 2760 - 3450	
HOSE LENGTH (FT. / M)	50 / 15.24	
HOSE DIAMETER (IN. / CM)	.75 / 1.90	1 / 2.54
WHEELS [SEMI-PNEUMATIC / STEEL] (IN. / CM)	16 X 4 / 40.64 X 10.16	36 X 6 / 91.44 X 15.24
USCG APPROVED	YES	

FEATURES:

- Stainless Steel Collars
- Chrome Plated Brass Fill Caps
- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Heavy Duty Hot Dipped Galvanized Steel Cylinder, Carriage, Hose Rack, and Wheels
- Lifting Eyes
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- DOT/TC Nitrogen Cylinder with Quick Opening Brass Valve
- 6 Year Warranty



DESIGNED AND ASSEMBLED IN USA

CHARGES

WATER & FOAM CHARGES

Charge 502, 22 oz. bottle ATC Foam – Model 250 & 254
Charge 506, 10 lb. carton Loaded Stream/Anti-Freeze – Model 240
Charge 506, 55 gal. drum Loaded Stream/Anti-Freeze - Model 240
Charge 534, 2 gal. pail ATC Foam – Model 630 & 631 Wheeled
3% AFFF Foam Concentrate
Class “A” Foam Concentrate
3 X 3 ATC Foam Concentrate



HALOTRON™ I CHARGES

Charge 890, 35 lb. cylinder
Charge 891, 80 lb. cylinder
Charge 892, 200 lb. cylinder



CLASS D DRY POWDER CHARGES

Charge 543, 35 lb. pail Graphite (G-Plus)
Charge 532, 300 lb. drum Graphite (G-Plus)
[Graphite applied to a metal fire using scoop or shovel]
Charge 557, 30 lb. pail Sodium Chloride (Super D) – Model B570 & 680
Charge 545, 50 lb. pail Sodium Chloride (Super D) – Model B570 & 680
[Sodium Chloride (Super D) may also be dispensed by a scoop or shovel]
Charge 548, 50 lb. pail Copper (Navy 125S) – Model B571 & 681



ABC DRY CHEMICAL CHARGES

Charge 552, 25 lb. pail
Charge 550, 50 lb. pail
Charge 555, 50 lb. pail – Model B402
Charge 540, 40 lb. carton
Charge 540-4, four 10 lb. bags in 40 lb. carton
Charge 509, 400 lb. drum



REGULAR DRY CHEMICAL CHARGES

Charge 512, 50 lb. pail
Charge 541, 40 lb. carton
Charge 511, 400 lb. drum



PURPLE K DRY CHEMICAL CHARGES

Charge 553, 25 lb. pail
Charge 515, 50 lb. pail
Charge 542, 40 lb. carton
Charge 517, 400 lb. drum



DESIGNED AND ASSEMBLED IN USA



Amerex Corporation

Quality is Behind the Diamond®

7595 Gadsden Hwy. • P.O. Box 81
Trussville, AL 35173
Ph: (205) 655-3271
Fax: 1-800-654-5980
Int'l Fax: (205) 655-0584

www.amerex-fire.com
sales@amerex-fire.com



ISO 9001 - Quality
ISO 14001 - Environmental
OHSAS 18001 - Safety
CERTIFIED FIRM

For more information please contact:



Amerex Corporation makes every attempt possible to provide the most current and updated information. Information contained within this brochure is deemed to be as accurate as possible as of the printing date. Routine changes to products, codes and standards, and warranties subsequent to this printing will supersede printed information. Please contact Amerex Corporation for any revisions, updates, or product changes.